

1 LOCATION OF WATER WELL:		Fraction SE 1/4 SW 1/4 SE 1/4		Section Number 15	Township Number T 14 S	Range Number R 3 (W)																																																
Distance and direction from nearest town or city street address of well if located within city? 671 Westport Blvd. Salina, Ks. 67401 MW 2																																																						
2 WATER WELL OWNER: Midway USA Conoco RR#, St. Address, Box #: 671 Westport Blvd. City, State, ZIP Code: Salina, Ks. 67401 Board of Agriculture, Division of Water Resources Application Number:																																																						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 37 ft. ELEVATION:																																																				
		Depth(s) Groundwater Encountered 1. 32 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 21.69 ft. below land surface measured on mo/day/yr 2-25-92 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7.5/8 in. to 37 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ☒																																																				
		5 TYPE OF BLANK CASING USED:																																																				
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded ☒ Blank casing diameter 2 in. to 17 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)																																																				
		SCREEN-PERFORATED INTERVALS: From 17 ft. to 37 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 15 ft. to 37 ft. From ft. to ft. From ft. to ft. From ft. to ft.																																																				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other																																																						
Grout Intervals: From 0 ft. to 12 (cement) ft. From 12 ft. to 15 (bent) ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Direction from well? Southwest How many feet? 150																																																						
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>6</td> <td>Silty clay, black</td> <td></td> <td></td> <td></td> </tr> <tr> <td>6</td> <td>11</td> <td>Silty clay, dark brown</td> <td></td> <td></td> <td>Flush Mount Cover</td> </tr> <tr> <td>11</td> <td>16.5</td> <td>Clay, brown</td> <td></td> <td></td> <td>KDHE Site ID# 00099314</td> </tr> <tr> <td>16.5</td> <td>25</td> <td>Silty clay, grey</td> <td></td> <td></td> <td></td> </tr> <tr> <td>25</td> <td>30</td> <td>Clay, grey</td> <td></td> <td></td> <td></td> </tr> <tr> <td>30</td> <td>32</td> <td>Sandy clay, grey</td> <td></td> <td></td> <td></td> </tr> <tr> <td>32</td> <td>37</td> <td>Sand, yellow, fine</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>							FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	6	Silty clay, black				6	11	Silty clay, dark brown			Flush Mount Cover	11	16.5	Clay, brown			KDHE Site ID# 00099314	16.5	25	Silty clay, grey				25	30	Clay, grey				30	32	Sandy clay, grey				32	37	Sand, yellow, fine			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																	
0	6	Silty clay, black																																																				
6	11	Silty clay, dark brown			Flush Mount Cover																																																	
11	16.5	Clay, brown			KDHE Site ID# 00099314																																																	
16.5	25	Silty clay, grey																																																				
25	30	Clay, grey																																																				
30	32	Sandy clay, grey																																																				
32	37	Sand, yellow, fine																																																				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-25-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 2-26-92 under the business name of GeoCore Services, Inc. by (signature) Dale A. Hill																																																						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																						