

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Saline	SW 1/4 SW 1/4 SW 1/4	18	T 14 S	R 3 EW

Distance and direction from nearest town or city street address of well if located within city?

1019 East Crawford, Salina, Ks.

2 WATER WELL OWNER:	Bill Reimold	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	1012 York Street	Application Number:
City, State, ZIP Code :	Salina, Ks. 67401	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 43 ft. ELEVATION: 27.57 ft. below land surface measured on mo/day/yr 06-11-93
	Depth(s) Groundwater Encountered 1. 30 ft. 2. 45 ft. 3. 57 ft. Pump test data: Well water was 7 5/8 in. to 45 ft. after 10 hours pumping 10 gpm Est. Yield 10 gpm: Well water was 7 5/8 in. to 45 ft. after 10 hours pumping 10 gpm Bore Hole Diameter 7 5/8 in. to 45 ft. and 10 in. to 57 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <input checked="" type="checkbox"/> No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted 06-11-93 Water Well Disinfected? Yes <input checked="" type="checkbox"/> No <input checked="" type="checkbox"/>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped <input checked="" type="checkbox"/>
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below) Welded <input checked="" type="checkbox"/>
2 PVC	4 ABS	7 Fiberglass	Threaded <input checked="" type="checkbox"/>
Blank casing diameter 2 in. to 27 ft. Dia 27 in. to 43 ft. Dia 43 in. to 57 ft.			
Casing height above land surface -3 in. weight 3 lbs./ft. Wall thickness or gauge No. Sch. 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	9 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 27 ft. to 43 ft. From 43 ft. to 57 ft.		
GRAVEL PACK INTERVALS:	From 25 ft. to 45 ft. From 45 ft. to 57 ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 0 ft. to 23 ft.	From 23 ft. to 25 ft.	From 25 ft. to 43 ft.	From 43 ft. to 57 ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well?	southwest	How many feet?	800	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4"	ASPHALT			
4"	3'	CLY, DK GY/BRN, MOD SLTY, MOIST			FLUSH MOUNT COVER
3	8	CLY, DK TO MED BRN, V SLTY, MOIST			MW17
8	12	SLT, LT BRN, V CLY, MOIST			Site Id # 00082040
12	19	CLY, LT MED BRN, V SLTY, MOIST			
19	21	SND, RD BRN, VF TO F, TR GRVL, W SRTD			
21	27	SND, MED TO LT GY/BRN, V F TO M, MOD SRTD			
27	34	CLY, OLIVE GY TO GY BRN, V SLTY			
34	45	SND, OLIVE GY, F TO CR, F TO C GRVL, P SRTD			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06-04-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 06-07-93 under the business name of GeoCore Services, Inc. by (signature) Doug Ray
