			WATE	ER WELL RECORD	Form \	MWC-5	KSA 82a-	1212		
1 LOCATI	ON OF WAT	TER WELL:	Fraction			Sec	tion Number	Township	Number	Range Number
County:			NW 1/4			<u> </u>	23	T 1.	4 s	R 3 EW
			wn or city street a	address of well if k	cated withir	city?				
	uth Broads	<u>:</u>					<u></u>			<u> </u>
<u> </u>	R WELL OW		rid Payne							
· · · ·	Address, Bo) W. North	34						Division of Water Resources
	, ZIP Code		ina, Ks. 6740						on Number:	
B LOCATI	E WELL'S L' IN SECTION	OCATION WITH N BOX:								
- ""		,			3 1	·				3
Ŧ	17	!								08-05-93
-	WW	NE								mag gniamı
1	1	•								mqing gpm
Mis M	!	E								i. to
λ .	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Speci									
	la _ \W = 1 = = \t = al					3 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well				
1 1		!!!	_					_	. 1	
<u>l</u> L		<u> </u>	mitted	rbacteriological san	ibie annuum	30 IO DI	•			, mo/day/yr sample was sub-
e Type (DE OLANK (CASING USED:	miteo	5 Wrought iron		Copor	ete tile	er Well Disinfed		No X
1 St		3 RMP (S	:R)	6 Asbestos-Cen						ied , Clamped
2 P\		4 ABS	···,	7 Fiberglass				,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		aded. X
			in to 23							in. to ft.
Casing he	ing urameter inht above I:	and surface	0	in weight		.111. 10	lhe /f		e or galiga N	lo. Sch. 40
				, weight		Ø₽V				
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steet				5 Fiberglass	_			10 Asbestos-cement 11 Other (specify)		
2 Brass 4 Galvanized steel				6 Concrete tile		9 AB			one used (o)	
		RATION OPENIN			5 Gauzed wrapped			8 Saw cut	٠.	11 None (open hole)
	ontinuous sto	_	Aill slot		6 Wire wrapped			9 Drilled hole:		i i i i i i i i i i i i i i i i i i i
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
SCREEN-PERFORATED INTERVALS: From										
										toft.
	GRAVEL PA	CK INTERVALS:	From	ft.	to	38	ft From	3	ft.	toft.
·			From	ft.	to		ft. From	າ		
6 GROUT	MATERIAL	: 1 Neat	cement	(2) Cement grout	(3) Bento	nite 4 (Other		
Grout Inte	rvals: Froi	m. , Q	.ft. to 17.	ft., From	17	ft.	to	ft., From .		ft. toft.
What is th	e nearest so	ource of possible	contamination:				10 Livesto	ock pens	14 A	bandoned water well
1 Septic tank 4 Lateral lines			7 Pit priv		1 Fuel storage			15 Oil well/Gas well		
2 Sewer lines 5 Cess pool				8 Sewage		12 Fertilizer storage 10			Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage										
Direction f		south			························		How man	y_ieer?		
FROM	TO 6"	CONCRETE	LITHOLOGIC	LOG	FF	MON_	то		PLUGGING I	NTERVALS
<u>6"</u>	3'		O C (SND)							·
3	7	OR/ERN, F TO	DAMP SNDY CL					Flush cov		
7	10	MOD BRN, DA		<u> </u>				Site TD #	00000431	
10	15.5	MOD GY, DAM						TANA I		
15.5	24	MOD GY, ERN								
24	30	MOD BRN, SL								
30	37	ERN, VERY S					-			
								· · · · · · · · · · · · · · · · · · ·		
										
- <u>-</u>							 - -			
			*** <u>**</u>				 			
		··· · ·								
7 CONTE		OR LANDOWNE	RIS CERTIFICATI	iON: This water	JI was 68 -	onot-	t		ah sanari	do a municipal de la company
										der my jurisdiction and was
completed on (mo/day/year)										
	business na		ecCore Servic		ei Yveli Meci	uiu Wa:	s completed of by (signatu	<i>A</i> 7	. ///-	· ፲ ኛ · · · · · · · · · · · · · · · · ·
							oy (Signatu	11 C) . W J Fill State		
	ICTIONS: Use to	nion like or patitivear	pen. PLEASE PRESS	FIRMLY and PRINT cles	rly. Please till in	blacks 4	underline or circle			dopies to Kansas Department