

1 LOCATION OF WATER WELL:		Fraction NW 1/4 NE 1/4 NW 1/4		Section Number 23	Township Number T 14 S	Range Number R 3 E/W
County: Saline						
Distance and direction from nearest town or city street address of well if located within city? 700 South Broadway						
2 WATER WELL OWNER: David Payne		Board of Agriculture, Division of Water Resources				
RR#, St. Address, Box # : 410 W. North		Application Number:				
City, State, ZIP Code : Salina, Ks. 67401						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL... 34 ft. ELEVATION:				
		Depth(s) Groundwater Encountered 1. 30 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 15.91 ft. below TOC measured on mo/day/yr 08-05-93 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7.5/8 in. to 34 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X.....; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X				
		5 TYPE OF BLANK CASING USED:				
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded X Blank casing diameter 2 in. to 14 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40				
		TYPE OF SCREEN OR PERFORATION MATERIAL:				
		1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)				
SCREEN-PERFORATED INTERVALS: From 14 ft. to 34 ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From 12 ft. to 34 ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout intervals: From 0 ft. to 3 ft., From 3 ft. to 12 ft., From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? Southwest How many feet? 165						
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS				
0	3'	Dark Brown, Clay	Flush cover			
3'	8'	Moderate Brown Clay	Site ID # 00080358			
8'	20'	Gray Clay, Trace Fine Sand	MW6			
20'	22'	Light Gray, Clay, Slightly Silty				
22'	34'	Rd./Brown, Clay, Silty, Fine, Sand				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 07-23-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 08-10-93 under the business name of GeoCore Services, Inc. by (signature) Doug Ray						
INSTRUCTIONS. Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						