		<del>+</del>	WELL HECOHD	Form vvv					
LOCATION OF WATER WELL: SALINEM		Fraction SW 1/	SW ,	NE .	Section Number	Township		Range N	
ounty:	on from nearest town	/4	- 74	74	24 N2	Т	14 s	R 3	E/W
istance and directi	on nom nearest town t	-	MINNEAPOLI		· <b>y</b> ·				
WATER WELL C	NAVNED CUANTO	KOMAREK	TITINDIN ODI						
WATER WELL C		MINNEAPOI	TS			Board of	F Agriculture 1	Division of Wate	ar Basaurcas
R#, St. Address, I ity, State, ZIP Cod		. KS. 6740					ion Number:	DIVISION OF WAR	er nesources
	LOCATION WITH 4			57	4 ELEVA				
AN "X" IN SECT	ON BOX: De	epth(s) Groundw	ater Encountered	1 1. 30	π. ELEVA ft. 2	ION: .+++	ft. 3		
I		ELL'S STATIC V	WATER LEVEL .	30	ft. below land surf	ace measured	on mo/day/yr	2-22-91	<u>.</u>
		Pump	test data: Well	water was	31 ft. af	ter <del>1</del>	hours pu	mping 30	) gpm
NW -	-  NE    Es				ft. af				
.					5.7ft., a				
w	T I W	ELL WATER TO	BE USED AS:	5 Public v	water supply	B Air conditioni	ng 11	Injection well	
1		1 Domestic	3 Feedlot	6 Oil field	water supply	9 Dewatering	12	Other (Specify	below)
sw -	-   SE	2 Irrigation	4 Industrial	7 Lawn a	nd garden only 1	0 Monitoring w	vell		
	l w	as a chemical/ba	acteriological sam	ple submitted t	o Department? Ye	sNo	X; If yes,	_mo/day/yr sam	nple was sub
	S mi	tted			Wat	er Well Disinfe	cted? Yes	X No	
TYPE OF BLANK	CASING USED:		5 Wrought iron	8 Cc	ncrete tile			J X Clam	ped
1 Steel	3 RMP (SR)		6 Asbestos-Cem	ent 9 Ot	her (specify below	)	Weld	ed	
2 PVC	4 ABS		7 Fiberglass				Threa	aded	
lank casing diamet	er 5 in.	to 47	ft., Dia	in	. to	ft., Dia		in. to	ft.
asing height above	aland surface16	) ii	n., weight	160	Ibs./f	t. Wall thicknes	s or gauge N	o SDR	26
	OR PERFORATION N				PVC_		sbestos-ceme		
1 Steel	3 Stainless st	eel	5 Fiberglass	8	RMP (SR)	11 C	Other (specify)		
2 Brass	4 Galvanized		6 Concrete tile		ABS	12 N	lone used (op	en hole)	
CREEN OR PERF	ORATION OPENINGS		5 G	Sauzed wrappe	d	8 Saw cut		11 None (ope	en hole)
1 Continuous	slot 3 Mill s	slot• 035	6 V	Vire wrapped		9 Drilled hole	s		
2 Louvered sh		punched	7 T	orch cut		10 Other (spec	cify)		
CREEN-PERFORA	TED INTERVALS:	From	47 ft. 1	to 57 .	ft., Fron	n <i></i>	ft. t	0	
					ft., Fron				
GRAVEL I	PACK INTERVALS:	From	<b>2.5</b> ft. 1	to	ft., Fror	n	ft. t	0	
		From	ft.	to	ft., Fror	n	ft. t	0	ft.
GROUT MATER	AL: 1 Neat cem	nent 2	Cement grout	<u>3 B</u>	entonite 4	Other			
rout Intervals: F	rom 0 ft.	to	ft., From		ft. to	ft., From	<b>.</b>	ft. to	
What is the nearest	source of possible con	ntamination:			10 Livest	ock pens	14 A	bandoned water	er well
1 Septic tank	4 Lateral I	ines	7 Pit privy	1	11 Fuels	storage	15 O	il well/Gas well	I
2 Sewer lines	5 Cess po	ol	8 Sewage	agoon	12 Fertili:	zer storage	16 O	ther (specify be	elow)
3 Watertight s	ewer lines 6 Seepage	e pit	9 Feedyar	rd	13 Insect	icide storage			
Direction from well?					How mar		20		
FROM TO		LITHOLOGIC L	OG	FRO	и то		PLUGGING I	NTERVALS	
0 3	TOP SOIL								
3 24	CLAY								
24 37	SAND & GRAV	ÆL							
37 38	CLAY								
38 57	MED. SAND 8	& GRAVEL							
	en remembro company de la partir de la company de company de la company de la company de la company de la comp								
			T						
							Mary 17 cm L . Mary Land Street Conference of the Conference of th		
	MARK OF SERVICE SERVIC	-/							
		· www. 1 hallow of the Manual to the control of the							***************************************
CONTRACTOR	S OR LANDOWNER'S	CERTIFICATIO	N: This water w	ell was (1) con	structed. (2) reco	nstructed, or (3	) plugged upo	der mv jurisdict	ion and was
ompleted on (mo/d	0 (	00 04				d is true to the		•	
	or's License No				was completed of	\ 1	#2_02 <u>-01</u>		
nder the business		GER PUMP S			by (signat		XT	estra	D
				arly Please fill in hi		4.0/	Sand ton three	copies to Jan 5	onartmact
	se typewriter or ball point pen onment, Bureau of Water, Top								epartment