


1 LOCATION OF WATER WELL: County: SALINE	Fraction: SW 1/4 NW 1/4 SW 1/4	Section Number: 27	Township Number: T 14 S	Range Number: R 3 E/W
--	---------------------------------------	---------------------------	--------------------------------	------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1901 HIGHLAND

2 WATER WELL OWNER: LARRY ZAHN RR#, St. Address, Box #: 1901 HIGHLAND City, State, ZIP Code: SALINA, KS 67401	Board of Agriculture, Division of Water Resources Application Number:
--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 58 ft. ELEVATION: 827-84 Depth(s) Groundwater Encountered 1. 28 ft. 2. 40 ft. 3. 90 ft. WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on mo/day/yr 827-84 Pump test data: Well water was 40 ft. after 1 hours pumping 90 gpm Est. Yield 40 gpm. Well water was 40 ft. after 1 hours pumping 90 gpm Bore Hole Diameter 8 1/2 in. to 48 ft. and 48 in. to 48 ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial X Lawn and garden only 9 Dewatering 12 Other (Specify below) Observation well Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No X
--	--

5 TYPE OF BLANK CASING USED: 1 Steel X PVC 3 RMP (SR) 4 ABS Blank casing diameter 5 in. to 53 in. Dia. 12 in. weight 160 lbs./ft. Wall thickness or gauge No. SDR 26 Casing height above land surface 12 in. weight 160 lbs./ft. Wall thickness or gauge No. SDR 26 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass X PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped X Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 53 ft. to 58 ft. From 58 ft. to 58 ft. From 58 ft. to 58 ft. GRAVEL PACK INTERVALS: From NONE ft. to NONE ft. From NONE ft. to NONE ft. From NONE ft. to NONE ft.	CASING JOINTS: Glued X Clamped Welded Threaded
---	---

6 GROUT MATERIAL: X Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 1 ft. to 10 ft. From 10 ft. to 10 ft. From 10 ft. to 10 ft. From 10 ft. to 10 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? NORTH How many feet? 90
--

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
1	9	TOP SOIL			
10	27	SANDY LOAM			
28	29	CLAY			
30	46	FINE SAND			
47	48	CLAY			
49	58	MED SAND			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was X constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-29-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 388 This Water Well Record was completed on (mo/day/yr) 8-29-84 under the business name of PESTINGER PUMP SERVICE by (signature) Don P. Pester INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.
--

OFFICE USE ONLY

T

R

3

E

SEC.

24

SW 1/4 NW 1/4 SW 1/4

SW 1/4 NW 1/4 SW 1/4

SW 1/4 NW 1/4 SW 1/4

SW 1/4 NW 1/4 SW 1/4

SW 1/4 NW 1/4 SW 1/4

SW 1/4 NW 1/4 SW 1/4

SW 1/4 NW 1/4 SW 1/4

SW 1/4 NW 1/4 SW 1/4

SW 1/4 NW 1/4 SW 1/4