

1 LOCATION OF WATER WELL: County: SALINE	Fraction NE 1/4 NE 1/4 SE 1/4	Section Number 24	Township Number T 14 S	Range Number R 3 E/W
--	---	-----------------------------	----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1219 Mc Adams

2 WATER WELL OWNER: JERRY SCOTT RR#, St. Address, Box #: 1219 Mc Adams City, State, ZIP Code: SALINA, KS 67401	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 54 ft. ELEVATION: 1100
--	---

	Depth(s) Groundwater Encountered 1. 21 ft. 2. . ft. 3. . ft.
	WELL'S STATIC WATER LEVEL 21 ft. below land surface measured on mo/day/yr
	Pump test data: Well water was 25 ft. after 1 hours pumping 40 gpm
	Est. Yield . gpm Well water was . ft. after . hours pumping . gpm
	Bore Hole Diameter 8 in. to 50 ft. and . in. to . ft.
WELL WATER TO BE USED AS:	
1 Domestic	5 Public water supply
3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial
	X Lawn and garden only
	10 Observation well
Was a chemical/bacteriological sample submitted to Department? Yes . No X ; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes . No X	

5 TYPE OF BLANK CASING USED:	3 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped .
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded .
X PVC	7 Fiberglass		Threaded .
Blank casing diameter . 5 in. to 49 ft., Dia . in. to . ft., Dia . in. to . ft.			
Casing height above land surface . 12 in., weight 160 lbs./ft. Wall thickness or gauge No. S&P 26			

TYPE OF SCREEN OR PERFORATION MATERIAL:	X PVC	10 Asbestos-cement
1 Steel	8 RMP (SR)	11 Other (specify) .
2 Brass	9 ABS	12 None used (open hole)
3 Stainless steel		
4 Galvanized steel		

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	X Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify) .	
4 Key punched			

SCREEN-PERFORATED INTERVALS:	From 49 ft. to 54 ft., From . ft. to . ft.
GRAVEL PACK INTERVALS:	From NONE ft. to . ft., From . ft. to . ft.

6 GROUT MATERIAL:	1 Neat cement	X Cement grout	3 Bentonite	4 Other .
Grout Intervals:	From 1 ft. to 10 ft., From . ft. to . ft.			

What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well
1 Septic tank	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)
X Watertight sewer lines	13 Insecticide storage	
4 Lateral lines		
5 Cess pool		
6 Seepage pit		
7 Pit privy		
8 Sewage lagoon		
9 Feedyard		
Direction from well?	How many feet? 40	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
1	7	TOPSOIL			
8	29	CLAY			
30	31	HEAVY GRAVEL			
32	33	CLAY			
34	54	MED GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) MAR 5, 1985 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 9885 This Water Well Record was completed on (mo/day/yr) MAR 5, 1985 under the business name of PESTINGIER DUMP SERVICE by (signature) Paul S. Pestingier
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.