WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL	Fraction	Section Number	Township Number	Range Number
County: Salina	X NE ¼ NW ¼ NW ¼	24	T 14 S	R 3 E (W)

Distance and direction from nearest town or city?

Street address of well if located within city? 707 Guernsey

2 WATER WELL OWNER: R. W. Bull
RR#, St. Address, Box # : 707 Guernsey
City, State, ZIP Code : Salina, Ks. 67401

Board of Agriculture, Division of Water Resources Application Number:

3 DEPTH OF COMPLETED WELL 49 ft. Bore Hole Diameter 8½ in. to ft., and in. to ft.

Well Water to be used as: 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply X Lawn and garden only 8 Air conditioning 9 Dewatering 10 Observation well 11 Injection well 12 Other (Specify below)

Well's static water level 31 ft. below land surface measured on 3 month 20 day 81 year

Pump Test Data: Well water was 41 ft. after 3 hours pumping 13 gpm
Est. Yield 30 gpm: Well water was ft. after hours pumping gpm

4 TYPE OF BLANK CASING USED: 1 Steel 2 PVC X RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below)

Casing Joints: Glued X Clamped Welded Threaded

Blank casing dia 5 in. to 49 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 12 in., weight 200 lbs./ft. Wall thickness or gauge No X 214

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC X RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)

Screen or Perforation Openings Are: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut X Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)

Screen-Perforation Dia 5 in. to 5 ft., Dia in. to ft., Dia in to ft.

Screen-Perforated Intervals: From 44 ft. to 49 ft., From ft. to ft.
From ft. to ft., From ft. to ft.

Gravel Pack Intervals: From ft. to ft., From ft. to ft.
From ft. to ft., From ft. to ft.

5 GROUT MATERIAL: 1 Neat cement X2 Cement grout 3 Bentonite 4 Other

Grouted Intervals: From 1 ft. to 10 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:
1 Septic tank 2 Sewer lines 3 Lateral lines 4 Cess pool 5 Seepage pit 6 Pit privy 7 Sewage lagoon 8 Feed yard 9 Livestock pens 10 Fuel storage 11 Fertilizer storage 12 Insecticide storage X13 Watertight sewer lines 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)

Direction from well East How many feet Over 50 ? Water Well Disinfected? Yes X No

Was a chemical/bacteriological sample submitted to Department? Yes No X : If yes, date sample was submitted month day year: Pump Installed? Yes X No

If Yes: Pump Manufacturer's name Webtrol Model No. 102s58b HP ½ Volts 230

Depth of Pump Intake 45 ft. Pumps Capacity rated at 13 gal./min.

Type of pump: X1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was X(1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on March month 2 day 81 year and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 388

This Water Well Record was completed on March month 31 day 81 year under the business name of Pestinger Pump Service by (signature) X [signature]

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: X



ELEVATION:

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
1	21	dirt			
22	35	Fine Sand			
36	49	Small Gravel			

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. 4 ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, *please press firmly* and *PRINT* clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T 14 R 3 E W SEC. 24 NE ¼ NW ¼ NW ¼