

1 LOCATION OF WATER WELL: County: Saline	Fraction SE 1/4 SW 1/4 NE 1/4	Section Number 25	Township Number T 14 S	Range Number R 3 EW
--	--------------------------------------	--------------------------	-------------------------------	----------------------------

Distance and direction from nearest town or city street address of well if located within city?

2092 NORTON

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code	LEONARD SCHMIDT 2092 NORTON SALINA, KS 67401	Board of Agriculture, Division of Water Resources Application Number:
---	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 55 ft. ELEVATION: 1235
--	---

Depth(s) Groundwater Encountered 1. **25** ft. 2. **25** ft. 3. **25** ft.

WELL'S STATIC WATER LEVEL **23** ft. below land surface measured on mo/day/yr **4-27-92**

Pump test data: Well water was **25** ft. after **1** hours pumping **15** gpm

Est. Yield **30** gpm. Well water was **25** ft. after **1** hours pumping **15** gpm

Bore Hole Diameter **8 1/2** in. to **25** ft., and **5 1/2** in. to **55** ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes **X** No **X** If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes **X** No **X**

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 45 ft. Dia			Threaded
Casing height above land surface 18 in. weight 160 lbs.			Wall thickness or gauge No. 5 DR 26
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 45 ft. to 55 ft.		
GRAVEL PACK INTERVALS:	From 22 ft. to 55 ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 22 ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? South			How many feet? 26 ft.	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	5'	Compacted dirt +			
5'	8'	Silt			
		Hard dark clay			
8'	15'	fine sand + clay			
15'	18'	mixed			
		Fine Sand			
18'	32'	Fine sand + clay			
		mixed			
32'	44'	Fine Sand			
44'	55'	Medium to Coarse Sand + Gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-27-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 523 This Water Well Record was completed on (mo/day/yr) 4-28-92 under the business name of M+D Well Service by (signature) Matthew Jorhup
--