

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SALINE		SE ¼ SW ¼ NW ¼	25	T 14 S	R 3 E/W
Distance and direction from nearest town or city street address of well if located within city? 1838 LEWIS					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		JOHN SIEFKER 1838 LEWIS SALINA, KS. 67401			
		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL. 52 ft. ELEVATION: 1240			
		Depth(s) Groundwater Encountered 1 29½ ft. 2. .ft. 3. .ft.			
		WELL'S STATIC WATER LEVEL 28½ ft. below land surface measured on mo/day/yr 10-16-91			
		Pump test data: Well water was 29½ ft. after 1 hours pumping 35 gpm			
		Est. Yield 75+ gpm; Well water was .ft. after .hours pumping .gpm			
		Bore Hole Diameter .9 in. to 52 .ft., and .in. to .ft.			
		WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes.....No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped .			
1 Steel 3 RMP (SR)		6 Concrete tile Welded .			
2 PVC 4 ABS		9 Other (specify below) Threaded .			
Blank casing diameter .5 in. to 42 ft., Dia .		Casing height above land surface 24 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 26			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) .		12 None used (open hole)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot .030 6 Wire wrapped 9 Drilled holes		7 Torch cut 10 Other (specify) .			
2 Louvered shutter 4 Key punched					
SCREEN-PERFORATED INTERVALS:		From 42 ft. to 52 ft., From .ft. to .ft.			
GRAVEL PACK INTERVALS:		From 35 ft. to 52 ft., From .ft. to .ft.			
FROM .ft. to .ft., FROM .ft. to .ft.					
6 GROUT MATERIAL:		3 Bentonite 4 Other .			
Grout Intervals: From 0 ft. to 20 ft., From .ft. to .ft., From .ft. to .ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		How many feet? 30			
Direction from well? SOUTH					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	TOP SOIL			
2	21	CLAY GRAY			
21	45	MED. SAND			
45	46	CLAY GRAY			
46	52	MED SAND & SMALL GRAVEL			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-16-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 388 This Water Well Record was completed on (mo/day/yr) 10-16-91 under the business name of PESTINGER PUMP SERVICE by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					