

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SALINE		NE 1/4 SE 1/4 NW 1/4	25	T 14 S	R 3 E
Distance and direction from nearest town or city street address of well if located within city? 2057 RAYMOND					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :		Salina, KANSAS 67401			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 53 ft. ELEVATION: 1231			
		Depth(s) Groundwater Encountered 1. 25 ft. 2. 25 ft. 3. 25 ft.			
		WELL'S STATIC WATER LEVEL 26 ft. below land surface measured on mo/day/yr 3-13-92			
		Pump test data: Well water was 31 ft. after 1 hours pumping 15 gpm			
		Est. Yield 25 gpm; Well water was 31 ft. after 1 hours pumping 15 gpm			
		Bore Hole Diameter 8 1/2 in. to 29 ft. and 5 1/2 in. to 53 ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Dewatering 12 Other (Specify below)			
		Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped X			
1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter 5 in. to 43 ft., Dia 43 in. to 43 ft., Dia 43 in. to 43 ft.		Welded X Threaded X			
Casing height above land surface 20 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 26					
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		11 Other (specify) 17 PVC			
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes		10 Other (specify) 17 Torch cut			
SCREEN-PERFORATED INTERVALS:					
From 43 ft. to 53 ft., From 43 ft. to 53 ft., From 43 ft. to 53 ft.					
GRAVEL PACK INTERVALS:					
From 20 ft. to 53 ft., From 20 ft. to 53 ft., From 20 ft. to 53 ft.					
6 GROUT MATERIAL:		4 Other 17 PVC			
Grout Intervals: From 0 ft. to 20 ft., From 0 ft. to 20 ft., From 0 ft. to 20 ft.		10 Livestock pens 14 Abandoned water well			
What is the nearest source of possible contamination:		11 Fuel storage 15 Oil well/Gas well			
1 Septic tank 4 Lateral lines 7 Pit privy 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 2 Sewer lines 5 Cess pool 9 Feedyard 13 Insecticide storage		How many feet? 45			
Direction from well? West					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	3'	Compacted dirt + silt			
3'	9'	FINE SAND + BROWN clay mixed			
9'	12'	FINE SAND			
12'	15'	DARK BROWN clay			
15'	29'	FINE SAND AND light BROWN clay			
29'	35'	medium to fine SAND			
35'	36'	Brown clay			
36'	53'	medium to coarse SAND			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-13-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 523 This Water Well Record was completed on (mo/day/yr) 3-13-92 under the business name of M&D Well Service by (signature) Matthew Loukup					