WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL

County: Saline | Fraction: NE ¼ NE ¼ SW ¼ | Section Number: 25 | Township Number: T 14 S | Range Number: R 3 W E/W

Distance and direction from nearest town or city?

Street address of well if located within city? 2112 Raymond, Salina Kans

2 WATER WELL OWNER: Denis Knipp

RR#, St. Address, Box # : 2112 Raymond

City, State, ZIP Code : Salina Kans 67401

Board of Agriculture, Division of Water Resources Application Number:

3 DEPTH OF COMPLETED WELL 57 ft. Bore Hole Diameter 6 in. to ft., and in. to ft.

Well Water to be used as:
1 Domestic 3 Feedlot 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Observation well 11 Injection well 12 Other (Specify below)
2 Irrigation 4 Industrial

Well's static water level 18 ft. below land surface measured on June month 15 day 1981 year

Pump Test Data: Well water was ND ft. after 1/2 hours pumping 30 gpm

Est. Yield 50 gpm: Well water was ft. after hours pumping gpm

4 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 6 Asbestos-Cement 8 Concrete tile 9 Other (specify below)
2 PVC 4 ABS 7 Fiberglass

Casing Joints: Glued Clamped Welded Threaded

Blank casing dia 4 in. to 48 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No SDR 26

TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 9 ABS 11 Other (specify) 12 None used (open hole)

Screen or Perforation Openings Are:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)

Screen-Perforation Dia 4 in. to 51 ft., Dia in. to ft., Dia in to ft.

Screen-Perforated Intervals: From 48 ft. to 51 ft., From ft. to ft.
From ft. to ft., From ft. to ft.

Gravel Pack Intervals: From 35 ft. to 51 ft., From ft. to ft.
From ft. to ft., From ft. to ft.

5 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grouted Intervals: From 3 ft. to 13 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:
1 Septic tank 4 Cess pool 7 Sewage lagoon 10 Fuel storage 14 Abandoned water well
2 Sewer lines 5 Seepage pit 8 Feed yard 11 Fertilizer storage 15 Oil well/Gas well
3 Lateral lines 6 Pit privy 9 Livestock pens 12 Insecticide storage 16 Other (specify below)
13 Watertight sewer lines

Direction from well west How many feet 70 ? Water Well Disinfected? Yes No

Was a chemical/bacteriological sample submitted to Department? Yes No: If yes, date sample was submitted month day year: Pump Installed? Yes No

If Yes: Pump Manufacturer's name Model No. HP Volts

Depth of Pump Intake ft. Pumps Capacity rated at gal./min.

Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on June month 15 day 1981 year and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 126

This Water Well Record was completed on June month 19 day 1981 year under the business name of Hydraulic Drilling Co by (signature) [illegible]

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



ELEVATION:

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	21	Clay, tan			
21	34	Sand, fine to medium			
34	51	Gravel & sand			

Depth(s) Groundwater Encountered 1. 18 ft. 2. ft. 3. ft. 4. ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, *please press firmly* and *PRINT* clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T 14 R 3 E/W SEC. 25 NE ¼ NE ¼ SW ¼