

1 LOCATION OF WATER WELL: County: Saline		Fraction SE ¼ NE ¼ SE ¼	Section Number 26	Township Number T 14 S	Range Number R 3 E
Distance and direction from nearest town or city street address of well if located within city? 2222 South Ninth, Salina, Kansas					
2 WATER WELL OWNER: Warta Buick RR#, St. Address, Box # : 2222 S. Ninth City, State, ZIP Code : Salina, Ks. 67401		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N --- NW --- NE --- W --- SW --- SE --- X S		4 DEPTH OF COMPLETED WELL.....27 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 18 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 18.6 ft. below land surface measured on mo/day/yr 06-14-93 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter .7 5/8 in. to 27 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter 2 in. to 12 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 30 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40		CASING JOINTS: Glued Clamped Welded Threaded X			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)		SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 12 ft. to 27 ft., From ft. to ft.		GRAVEL PACK INTERVALS: From 10 ft. to 27 ft., From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From 0 ft. to 8 ft., From 8 ft. to 10 ft., From ft. to ft.			
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? southeast How many feet? 230					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	CLAY, DK BRN, SILTY			
3	6	SILTY, LT BRN, CLAYEY			
6	17	CLAY, MOD BRN, V SLTY			
17	19	CLAY, MOD-DK BRN, SL SLTY			
19	27	CLAY, DK RD/BRN, SL SLTY, MOD SNDY			
MW9 Above ground cover KDHE site id 00080570					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06-21-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 07-01-93 by (signature) GeoCore Services, Inc.					

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.