

1 LOCATION OF WATER WELL: County: Saline		Fraction SW 1/4 NE 1/4 NE 1/4		Section Number 36		Township Number T 14 S		Range Number R 3		W	
Distance and direction from nearest town or city street address of well if located within city? In City Limits-3631 Brett, Salina											
2 WATER WELL OWNER: Sara Houser RR#, St. Address, Box # : 3631 Brett City, State, ZIP Code : Salina, KS 67401 Board of Agriculture, Division of Water Resources Application Number:											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL 60 ft. ELEVATION: Depth(s) Groundwater Encountered 1 20 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr 4/10/90 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 70 gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 60 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No								
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 5 in. to 50 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 12 in., weight 2.91 lbs./ft. Wall thickness or gauge No. 265 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 50 ft. to 60 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 60 ft. From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? East How many feet? 50ft FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 2 Top Soil 2 20 Gray Clay 20 29 Silty Clay 29 60 Fine to Medium Sands 60 Shale 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/10/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 4-13-90 under the business name of Peterson Irrigation, Inc. by (signature) Mike Peterson INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.											