

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>SALINE</u>		<u>SW 1/4 NE 1/4 SE 1/4</u>	<u>36</u>	T <u>14 S</u>	R <u>3 E</u>
Distance and direction from nearest town or city street address of well if located within city? <u>2814 Melaine Lane</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #:		Application Number:			
City, State, ZIP Code:		<u>Salina, Kansas 67401</u>			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>53</u> ft. ELEVATION: <u>1241</u>			
		Depth(s) Groundwater Encountered 1. <u>25'</u> ft. 2. <u>25'</u> ft. 3. <u>25'</u> ft.			
		WELL'S STATIC WATER LEVEL <u>25'</u> ft. below land surface measured on mo/day/yr <u>4-12-92</u>			
		Pump test data: Well water was <u>25 1/2</u> ft. after <u>12</u> hours pumping <u>15</u> gpm			
		Est. Yield <u>30</u> gpm Well water was <u>25</u> ft. after <u>12</u> hours pumping <u>15</u> gpm			
		Bore Hole Diameter <u>8 1/2</u> in. to <u>25</u> ft., and <u>15</u> in. to <u>25</u> ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u>		If yes, mo/day/yr sample was submitted <u>4-12-92</u>			
5 TYPE OF BLANK CASING USED:		Water Well Disinfected? Yes <u>X</u> No <u>X</u>			
1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped <u>X</u> 6 Asbestos-Cement 9 Other (specify below) Welded <u>X</u> 7 Fiberglass Threaded <u>X</u>			
Blank casing diameter <u>5</u> in. to <u>43</u> ft., Dia <u>18</u> in. weight <u>160 LB</u> lbs./ft. Wall thickness or gauge No. <u>SDR 26</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 10 Asbestos-cement 11 Other (specify) <u>SDR 26</u> 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		1 Continuous slot 2 Mill slot 3 Gauzed wrapped 8 Saw cut 11 None (open hole) 4 Louvered shutter 5 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From <u>43</u> ft. to <u>53</u> ft., From <u>53</u> ft. to <u>53</u> ft. From <u>20</u> ft. to <u>53</u> ft., From <u>53</u> ft. to <u>53</u> ft.			
GRAVEL PACK INTERVALS:		From <u>20</u> ft. to <u>53</u> ft., From <u>53</u> ft. to <u>53</u> ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other <u>45'</u> Grout Intervals: From <u>0</u> ft. to <u>20</u> ft., From <u>20</u> ft. to <u>53</u> ft., From <u>53</u> ft. to <u>53</u> ft.			
What is the nearest source of possible contamination:		1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)			
Direction from well? <u>EAST</u>		How many feet? <u>45'</u>			
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0'	6'	Compacted dirt + clay			
6'	11'	clay + fine SAND			
11'	16'	mixed light brown clay			
16'	19'	clay + fine SAND			
19'	25'	mixed light brown clay			
25'	41'	medium to coarse SAND + gravel			
41'	43'	clay Dark grey			
43'	53'	Medium to coarse SAND + gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>4-12-92</u> and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. <u>523</u> This Water Well Record was completed on (mo/day/yr) <u>4-12-92</u>					
under the business name of <u>M&D Well Service</u> by (signature) <u>Matthew Soukup</u>					