

1 LOCATION OF WATER WELL: County: SALINE		Fraction SW $\frac{1}{4}$ NW $\frac{1}{4}$ SE $\frac{1}{4}$		Section Number 36	Township Number T 14 S	Range Number R 3 E/W																																																						
Distance and direction from nearest town or city street address of well if located within city? 2766 LINDA LANE																																																												
2 WATER WELL OWNER: ROBERT ALLEN RR#, St. Address, Box # : 2766 LINDA LANE City, State, ZIP Code : SALINA, KS. 67401 Board of Agriculture, Division of Water Resources Application Number:																																																												
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div><div>1 Mile</div><div><div>N</div><div>W</div><div>E</div><div>S</div><div><div>NW</div><div>NE</div><div>SW</div><div>SE</div><div>X</div></div></div></div>		4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 1241 Depth(s) Groundwater Encountered 1. 24 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 24 ft. below land surface measured on mo/day/yr 6-25-92 Pump test data: Well water was 25 ft. after 1 hours pumping 35 gpm Est. Yield 100 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 60 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial <u>7 Lawn and garden only</u> 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No																																																										
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped <u>2 PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter 5 in. to 55 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 18 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 26 TYPE OF SCREEN OR PERFORATION MATERIAL: <u>7 PVC</u> 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot <u>.030</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 55 6 Wire wrapped 9 Drilled holes 7 Torch cut 60 10 Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 35 ft. to 60 ft., From ft. to ft. From ft. to ft., From ft. to ft.																																																												
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other Grout Intervals: From 0 ft. to 21 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well <u>3 Watertight sewer lines</u> 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? WEST How many feet? 15																																																												
<table border="1"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>PLUGGING INTERVALS</th></tr></thead><tbody><tr><td>0</td><td>2</td><td>TOP SOIL</td><td></td><td></td><td></td></tr><tr><td>2</td><td>18</td><td>CLAY LIGHT GRAY</td><td></td><td></td><td></td></tr><tr><td>18</td><td>26</td><td>CLAY TAN SILTY</td><td></td><td></td><td></td></tr><tr><td>26</td><td>36</td><td>SAND FINE</td><td></td><td></td><td></td></tr><tr><td>36</td><td>38</td><td>CLAY TAN</td><td></td><td></td><td></td></tr><tr><td>38</td><td>51</td><td>SAND COARSE</td><td></td><td></td><td></td></tr><tr><td>51</td><td>52</td><td>CLAY TAN</td><td></td><td></td><td></td></tr><tr><td>52</td><td>60</td><td>SAND COARSE & SMALL GRAVEL</td><td></td><td></td><td></td></tr></tbody></table>							FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	2	TOP SOIL				2	18	CLAY LIGHT GRAY				18	26	CLAY TAN SILTY				26	36	SAND FINE				36	38	CLAY TAN				38	51	SAND COARSE				51	52	CLAY TAN				52	60	SAND COARSE & SMALL GRAVEL			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																							
0	2	TOP SOIL																																																										
2	18	CLAY LIGHT GRAY																																																										
18	26	CLAY TAN SILTY																																																										
26	36	SAND FINE																																																										
36	38	CLAY TAN																																																										
38	51	SAND COARSE																																																										
51	52	CLAY TAN																																																										
52	60	SAND COARSE & SMALL GRAVEL																																																										
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-25-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 388 This Water Well Record was completed on (mo/day/yr) 6-25-92 under the business name of PESTINGER PUMP SERVICE by (signature) <i>Paul Pestinger</i>																																																												
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																												