	WATER WELL	RECORD For	m WWC-5 KS	SA 82a-12			
LOCATION OF WATER WELL:	Fraction SE 1/4 SU	J ₄ NU	Section Nu	umber	Township Number		
County: SAINS Distance and direction from nearest town of					17	S R 5 E(W)	
Distance and direction from hearest town of	•	rland	itiliti City:				
		scher					
WATER WELL OWNER:	- '				Doord of Acrie	lture, Division of Water Resources	
RR#, St. Address, Box # :		orland	6740	n /			
		NSAS _					
LOCATE WELL'S LOCATION WITH 4 AN "X" IN SECTION BOX:	DEPTH OF COMPLET	red Well	1. 🚖 ft. E	ELEVATIO	DN:	· . J	
N De	pth(s) Groundwater Er	countered 1	J.5	ft. 2		. ft. 3	
₹	ELL'S STATIC WATER	LEVEL . 2.5	ft. below la	ind surfac	e measured on mo/	day/yr /025-92	
NW _ NE						urs pumping/.5 gpm	
			as	. ft. after	ho	urs pumping gpm	
Bo	re Hole Diameter		_		5. <i>!</i> 2.	in. to 5	
WE WE	ELL WATER TO BE U		Public water suppl	-	Air conditioning	11 Injection well	
ī	1 Domestic 3	Feedlot 6	Oil field water sup	ply 9	Dewatering	12 Other (Specify below)	
	•		-	•		.,	
Wa	as a chemical/bacteriok	ogical sample sub	mitted to Departme	ent? Yes	No	If yes, mo/day/yr sample was sub-	
<u>S</u> mit	tted			Water	Well Disinfected? `	res K No	
TYPE OF BLANK CASING USED:	5 Wro	ught iron	8 Concrete tile		CASING JOINTS	: Glued . 💢 Clamped	
1 Steel 3 RMP (SR)	6 Asbe	stos-Cement	9 Other (specify	y below)		Welded	
(2) PVC 4 ABS	7 Fibe	rglass				Threaded	
Blank casing diameter in.	to 7: 🚣 ft	., Dia	ip. to		.ft., Dia	in. to ft.	
Casing height above land surface	& in., wei	ght		. lbs./ft. \	Wall thickness or ga	uge No. 50. K. 2. 6	
TYPE OF SCREEN OR PERFORATION M	MATERIAL:		GD PVC		10 Asbesto	s-cement	
1 Steel 3 Stainless steel		5 Fiberglass 8 RMP (SR))	11 Other (specify)		
2 Brass 4 Galvanized steel		6 Concrete tile 9 ABS			12 None us	ed (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		C	Saw cut	11 None (open hole)	
1 Continuous slot 3 Mill s	lot	6 Wire wra	pped	9	Drilled holes		
2 Louvered shutter 4 Key p	4 ,	7 Torch cu	^t ~ 3	10	Other (specify)		
SCREEN-PERFORATED INTERVALS:	From		_			ft. to	
	From	ft. to				ft. to	
GRAVEL PACK INTERVALS:	From	ft. to	5 .). f	ft., From .		. ft. to	
	From	ft. to		ft., From		ft. to ft.	
GROUT MATERIAL: Geat cem	7 1	nt grout	3 Bentonite				
Grout Intervals: From	to ft.,	From	ft. to		. ft., From	ft. to ft.	
What is the nearest source of possible contamination:				10 Livestock pens		14 Abandoned water well	
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel storage		15 Oil well/Gas well	
2 Sewer lines 5 Cess pool		B Sewage lagoon		12 Fertilizer storage		16 Other (specify below)	
3 Vatertight sewer lines 6 Seepage pit		9 Feedyard		13 Insecticide storage		÷····	
Direction from well?	2 A S [ow many 1		teet	
	LITHOLOGIC LOG	Compa	FROM TO	<u> </u>	PLUGO	SING INTERVALS	
	I AND	compac	140				
al all dint t	3//	x					
2 37 8/44	(Brow M	シーー					
24' 20' 0/05	(anov)						
34, 36, clar	(7' = 1)						
39' 43' Clay	+ med.	m 5AA	. 7				
37 /3 = 127	i mearo	m Jan					
45/ 50/ 50	XEG	0 - 0 -					
43. 27 Westin	um 10	coarse					
- JAND	AND 3	rave 4					
01 01-1-1	1	D no L. A					
52 Clay	aarn	Brown					
	-						
	4,000						
	050515107-1-1-1						
CONTRACTOR'S OR LANDOWNER'S	CERTIFICATION: This	water well was				* *	
	273	The Market Committee of the Committee of				my knowledge and belief. Kansas	
Water Well Contractor's License No.	(3 × 3 · · · · · ·		Record was comp			0-261-7-4	
under the business name of) Well	Service	<u>by</u>	(signature	Muthe	wagerpup	

INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.