

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SALINE		SE 1/4 SE 1/4 NW 1/4	36	T 14 S	R 3 E
Distance and direction from nearest town or city street address of well if located within city? 2657 RAY					
2 WATER WELL OWNER: Jerome Burns					
RR#, St. Address, Box # : 2657 RAY			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : SALINA, KS 67401			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 56 ft. ELEVATION: 1241			
		Depth(s) Groundwater Encountered 1. 17 ft. 2. 15 ft. 3. 6-4-94 ft.			
		WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 6-4-94			
		Pump test data: Well water was 18 1/2 ft. after 1 hours pumping 35 gpm			
		Est. Yield 50 gpm; Well water was 18 1/2 ft. after 1 hours pumping 35 gpm			
		Bore Hole Diameter 8 1/2 in. to 21 ft. and 5 1/2 in. to 56 ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No X			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
				8 Concrete tile	
				9 Other (specify below)	
				CASING JOINTS: Glued X Clamped	
				Welded	
				Threaded	
Blank casing diameter 5 in. to 46 ft. Dia 18 in. to 160 lbs./ft. Wall thickness or gauge No. SDR 26					
Casing height above land surface 18 in., weight 160 lbs./ft.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel		5 Fiberglass	
2 Brass		4 Galvanized steel		6 Concrete tile	
				8 RMP (SR)	
				9 ABS	
				10 Asbestos-cement	
				11 Other (specify)	
				12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot		5 Gauzed wrapped	
2 Louvered shutter		4 Key punched		6 Wire wrapped	
				7 Torch cut	
				8 Saw cut	
				9 Drilled holes	
				10 Other (specify)	
				11 None (open hole)	
SCREEN-PERFORATED INTERVALS: From 46 ft. to 56 ft. From 46 ft. to 56 ft. From 46 ft. to 56 ft.					
GRAVEL PACK INTERVALS: From 21 ft. to 56 ft. From 21 ft. to 56 ft. From 21 ft. to 56 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 21 ft. From 0 ft. to 21 ft. From 0 ft. to 21 ft. From 0 ft. to 21 ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
				10 Livestock pens	
				11 Fuel storage	
				12 Fertilizer storage	
				13 Insecticide storage	
				14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below)	
Direction from well? North				How many feet? 17 ft	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	3'	Compacted dirt & silt			
3'	20'	Loam sand & clay mixed			
20'	22'	clay (light brown)			
22'	27'	sand and clay mixed			
27'	35'	Fine sand			
35'	36'	clay (brown)			
36'	56'	medium to coarse sand			
56'		shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-5-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 523 This Water Well Record was completed on (mo/day/yr) 6-12-94 under the business name of M & D Well Service by (signature) Matthew Jorjup					