

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Saline	SE 1/4 SE 1/4 SE 1/4	12	T 14 S	R 3

Distance and direction from nearest town or city street address of well if located within city?

In City Limits-1020 Johnstown, Salina

2 WATER WELL OWNER:	Roy Wells	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #	1020 Johnstown	Application Number:
City, State, ZIP Code	Salina, KS 67401	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 56 ft. ELEVATION:
--	---

	Depth(s) Groundwater Encountered 1. 30 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr 10-18-94
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield 45-50 gpm: Well water was 35 ft. after 1 hours pumping 8 gpm
Bore Hole Diameter 8 in. to 60 ft. and in. to ft.	
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	5 Public water supply 8 Air conditioning 11 Injection well
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	3 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
1 Steel 3 RMP (SR)	6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 4 ABS	7 Fiberglass Threaded

Blank casing diameter 5 in. to 46 ft. Dia. in. to ft. Dia. in. to ft.
Casing height above land surface 12 in. weight 2.37 lbs./ft. Wall thickness or gauge No. .217

TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS:	From 46 ft. to 56 ft. From ft. to ft. From ft. to ft. From ft. to ft.
GRAVEL PACK INTERVALS:	From 25 ft. to 56 ft. From ft. to ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 5 ft. to 25 ft. From ft. to ft. From ft. to ft. From ft. to ft.	

What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	

Direction from well? North	How many feet? 225 ft
-----------------------------------	------------------------------

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top Soil			
2	12	Brick & Boards/Backfill			
12	23	Gray Clay			
23	44	Fine to Medium Sand			
44	60	Medium Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-18-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 10-24-94 under the business name of Peterson Irrigation Inc. by (signature) Mike Peterson
