

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Saline	NW 1/4 SE 1/4 NW 1/4	13	T 14 S	R 3 W E/W

Distance and direction from nearest town or city street address of well if located within city?

S.E. Corner of 4th and Walnut Salina KS

2 WATER WELL OWNER:	This & That Lamps & Shades
RR#, St. Address, Box # :	618 E. Republic
City, State, ZIP Code :	Salina, Kansas 67401

Board of Agriculture, Division of Water Resources

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 1225
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 31.1 ft. below land surface measured on mo/day/yr 11/29/94
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield NA gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 8 in. to 40 ft., and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes.....No..... X ...; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 2 in. to 25 ft., Dia. in. to ft., Dia. in. to ft.			Threaded. X
Casing height above land surface -1.4 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 25 ft. to 40 ft., From ft. to ft.		
GRAVEL PACK INTERVALS:	From 23 ft. to 40 ft., From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 21 ft., From 21 ft. to 23 ft., From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	UST
Direction from well? Northeast			How many feet? 125	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Clay, Dark Brown			MW2
2	4	Clay, Dark Brown			GeoCore # 114118 Flush-mount Cover
4	7	Clay, Light Brown			KDHE # 05085854 Tag # 00111788
7	12	Clay, Medium Brown			
12	15	Clay, Light Yellow to Brown			
15	21	Clay, Medium to Light Brown			
21	30	Silt, Light Yellow to Brown			
30	34	Silt, Light Brown			
34	36	Sand, Medium Gray			
36	40	Sand, Dark Gray			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, 2 reconstructed, or 3 plugged under my jurisdiction and was completed on (mo/day/year) 11/29/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 12/14/94 under the business name of GeoCore Services, Inc. by (signature) <i>Paul A. Paul</i>
