

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Saline		NE 1/4 SE 1/4 NW 1/4	13	T 14 S	R 3 W E/W

Distance and direction from nearest town or city street address of well if located within city?
S.E. Corner of 3rd and Walnut Salina, KS

2 WATER WELL OWNER: This & That Lamps & Shades		Board of Agriculture, Division of Water Resources Application Number:
RR#, St. Address, Box # : 618 E. Republic		
City, State, ZIP Code : Salina, Kansas 67401		

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 1224
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 30.3 ft. below land surface measured on mo/day/yr 11/29/94
	Pump test data: Well water was ft. after hours pumping gpm Est. Yield NA gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 40 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No..... X ...; If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued Clamped	
1 Steel		3 RMP (SR)		6 Asbestos-Cement		9 Other (specify below) Welded	
2 PVC		4 ABS		7 Fiberglass		Threaded. X	
Blank casing diameter 2 in. to 25 ft., Dia in. to ft., Dia in. to ft.		Casing height above land surface -1 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel		3 Stainless steel		5 Fiberglass		7 PVC	
2 Brass		4 Galvanized steel		6 Concrete tile		8 RMP (SR)	
						9 ABS	
						10 Asbestos-cement	
						11 Other (specify)	
						12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot		3 Mill slot		5 Gauzed wrapped		8 Saw cut	
2 Louvered shutter		4 Key punched		6 Wire wrapped		9 Drilled holes	
				7 Torch cut		10 Other (specify)	
						11 None (open hole)	
SCREEN-PERFORATED INTERVALS: From 25 ft. to 40 ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 23 ft. to 40 ft., From ft. to ft.							

6 GROUT MATERIAL:		1 Neat cement		2 Cement grout		3 Bentonite		4 Other	
Grout Intervals: From 0 ft. to 21 ft., From 21 ft. to 23 ft., From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens		14 Abandoned water well	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage		15 Oil well/Gas well	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage		16 Other (specify below)	
						13 Insecticide storage		UST	
Direction from well? Northwest						How many feet? 300			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Clay, Dark Brown			MW4
2	4	Clay, Dark Brown			GeoCore # 114118 Flush-mount Cover
4	7	Clay, Light Yellow Brown			KDHE # 05085854 Tag # 00111740
7	11.5	Clay, Medium to Dark Brown			
11.5	15	Clay, Light Brown			
15	21	Clay, Medium Brown, Mottled with Gray			
21	25	Clay, Medium to Light Brown, Orange Ti			
25	30	Sand, Light Brown			
30	35	Sand, Yellow to Orange			
35	40	Sand, Yellow to Orange			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/29/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 12/14/94 under the business name of GeoCore Services, Inc. by (signature) <i>Dale A. Bell</i>	
---	--