

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Saline	SW $\frac{1}{4}$ NE $\frac{1}{4}$ NW $\frac{1}{4}$	13	T 14 S	R 3 W E/W

Distance and direction from nearest town or city street address of well if located within city?

N.E. Corner of 4th and Walnut Salina, KS

2 WATER WELL OWNER:	This & That Lamps & Shades	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	618 E. Republic	Application Number:
City, State, ZIP Code :	Salina, Kansas 67401	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 1225
--	---

	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 30.7 ft. below land surface measured on mo/day/yr 11/29/94
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield NA gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 8 in. to 40 ft., and in. to ft.
	WELL WATER TO BE USED AS:
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes.....No..... X If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 2 in. to 25 ft., Dia in. to ft., Dia in. to ft.			Threaded X
Casing height above land surface -1.2 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40			

TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	5 Fiberglass
2 Brass	4 Galvanized steel	6 Concrete tile
3 RMP (SR)	8 RMP (SR)	11 Other (specify)
4 ABS	9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)

SCREEN-PERFORATED INTERVALS:	From 25 ft. to 40 ft., From ft. to ft.
GRAVEL PACK INTERVALS:	From 23 ft. to 40 ft., From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 0 ft. to 21 ft., From 21 ft. to 23 ft., From ft. to ft.			

What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well
1 Septic tank	4 Lateral lines	7 Pit privy
2 Sewer lines	5 Cess pool	8 Sewage lagoon
3 Watertight sewer lines	6 Seepage pit	9 Feedyard
		11 Fuel storage
		12 Fertilizer storage
		13 Insecticide storage
		15 Other (specify below) UST

Direction from well?	Southeast	How many feet?	100
----------------------	------------------	----------------	------------

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.33	Concrete,			MW5
0.33	2	Clay, Medium Brown			GeoCore # 114118 Flush-mount Cover
2	4	Clay, Medium Brown, Slight Orange Tint			KDHE # 05085854 Tag # 00111801
4	5	Clay, Light Brown			
5	7	Clay, Light Brown			
7	10.5	Clay, Medium Brown			
10.5	14	Clay, Medium Gray, Mottled Brown			
15	21	Clay, Medium Gray to Brown			
21	22	Clay, Light Brown, Slight Orange Tint			
22	30	Clay, Medium Gray to Brown			
30	35	Sand, Light Gray to Brown			
35	40	Sand, Dark Gray			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:	This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/29/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 12/14/94 under the business name of GeoCore Services, Inc. by (signature) <i>Paul A. Bell</i>
--	--