

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Saline	SW $\frac{1}{4}$ NE $\frac{1}{4}$ NW $\frac{1}{4}$	13	T 14 S	R 3 W E/W

Distance and direction from nearest town or city street address of well if located within city?

N.W. Corner of 3rd and Walnut St. Salina, KS

2 WATER WELL OWNER:	This & That Lamps & Shades	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	618 E. Republic	Application Number:
City, State, ZIP Code :	Salina, Kansas 67401	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 1224
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 29.9 ft. below land surface measured on mo/day/yr 11/29/94
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield NA gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 8 in. to 40 in. to in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)	
Was a chemical/bacteriological sample submitted to Department? Yes.....No..... X ...; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below) Welded
2 PVC	4 ABS	7 Fiberglass	Threaded. X
Blank casing diameter 2 in. to 25 in. to ft. Dia. in. to ft. Dia. in. to ft.			
Casing height above land surface 2 in. weight lbs./ft. Wall thickness or gauge No. Sch. 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
10 Asbestos-cement	11 Other (specify)	12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
7 Torch cut	10 Other (specify)	11 None (open hole)	
SCREEN-PERFORATED INTERVALS: From 25 ft. to 40 ft. From ft. to ft.			
GRAVEL PACK INTERVALS: From 23 ft. to 25 ft. From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 21 ft. From 21 ft. to 23 ft. From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below) UST
Direction from well? West			How many feet? 225	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Clay, Dark Brown			MW6
2	3	Clay, Medium Brown, Slight Orange Tint			GeoCore # 114118 Flush-mount Cover
3	5	Clay, Medium Brown			KDHE # 05085854 Tag # 00111757
5	8	Clay, Medium to Dark Brown			
8	15	Clay, Medium Brown, Slight Orange Tint			
15	22	Clay, Light Brown, Slight Orange Tint			
22	25	Silt, Light Yellow to Brown			
25	30	Clay, Light Brown, Very Slight Orange Ti			
30	32	Sand, Light Gray			
32	35	Sand, Dark Gray			
35	40	Sand, Dark Gray			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/29/94 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 12/15/94
under the business name of GeoCore Services, Inc. by (signature) <i>Dale C. Bell</i>