

LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County:	Saline	SW ¼	NE ¼	NW ¼	13	T 14 S	R 3 W E/W		

Distance and direction from nearest town or city street address of well if located within city?

N.W. Corner of 4th and Walnut St. Salina, KS

WATER WELL OWNER:	This & That Lamps & Shades	
RR#, St. Address, Box # :	618 E. Republic	Board of Agriculture, Division of Water Resources
City, State, ZIP Code :	Salina, Kansas 67401	Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 40 ft. ELEVATION: 1225

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. 11/29/94

WELL'S STATIC WATER LEVEL 31. ft. below land surface measured on mo/day/yr

Pump test data: Well water was . ft. after . hours pumping . gpm

Est. Yield NA gpm Well water was . ft. after . hours pumping . gpm

Bore Hole Diameter. 8 in. to 40 ft., and . in. to . ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		0 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued	Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded	
2 PVC	4 ABS	7 Fiberglass		Threaded	X
Blank casing diameter 2 in. to 25 ft., Dia	 in. to ft., Dia	 in. to ft.	
Casing height above land surface -3.6 in., weight lbs./ft. Wall thickness or gauge No.		Sch. 40	

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 25 ft. to 40 ft., From ft. to ft.
From ft. to ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 23 ft. to 40 ft., From ft. to ft.
From ft. to ft., From ft. to ft.

3] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 21 ft. From 21 ft. to 23 ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	UST

Direction from well?	South	How many feet?	150
----------------------	-------	----------------	-----

[illegible]

7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/29/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 12/15/94 under the business name of GeoCore Services, Inc. by (signature) Dale A. Bell