

1] LOCATION OF WATER WELL: County: Saline	Fraction NW 1/4 SE 1/4 NW 1/4	Section Number 13	Township Number T 14 S	Range Number R 3 W E/W
---	---	-----------------------------	----------------------------------	----------------------------------

Distance and direction from nearest town or city street address of well if located within city?

200' S.E. of 4th and Walnut St. Salina

2] WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	This & That Lamps & Shades 618 E. Republic Salina, Kansas 67401	Board of Agriculture, Division of Water Resources Application Number:
--	--	--

3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4] DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 1225
---	--

Depth(s) Groundwater Encountered 1. **31.6** ft. 2. **11/29/94** ft. 3. **11/29/94** ft.

WELL'S STATIC WATER LEVEL **31.6** ft. below land surface measured on mo/day/yr **11/29/94**

Pump test data: Well water was **NA** ft. after **8** hours pumping **40** gpm

Est. Yield **NA** gpm: Well water was **8** ft. after **40** hours pumping **40** gpm

Bore Hole Diameter **8** in. to **40** ft., and **40** in. to **40** ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		0 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes **X** No **X**; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes **X** No **X**

5] TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped X
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded X
Blank casing diameter 2 in. to 25 ft., Dia 25 in. to 40 ft., Dia 40 in. to 40 ft.			Threaded X
Casing height above land surface -2.9 in., weight 25 lbs./ft. Wall thickness or gauge No. Sch. 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 25 ft. to 40 ft., From 40 ft. to 40 ft.		
GRAVEL PACK INTERVALS:	From 23 ft. to 40 ft., From 40 ft. to 40 ft.		

6] GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 21 ft., From 21 ft. to 23 ft., From 23 ft. to 40 ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	UST
Direction from well? Northeast			How many feet? 200	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Sand and Road Gravel,			MW10
0.5	2	Clay, Very Dark Brown			GeoCore # 114118 Flush-mount Cover
2	4	Clay, Medium Brown, Slight Orange Tint			KDHE # 05085854 Tag # 00111771
4	6	Silt, Light Yellow Brown			
6	10	Clay, Light Brown			
10	15	Clay, Medium Brown			
15	20	Clay, Medium to Light Brown, Slight Ora			
20	22	Clay, Light Brown, Slight Orange Tint			
22	25	Clay, Light Brown, Slight Orange Tint			
25	32.5	Clay, Light Medium Brown			
32.5	35	Sand, Light Brown, Slight Orange Tint			
35	40	Sand, Light Brown			

7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, 2 reconstructed, or 3 plugged under my jurisdiction and was completed on (mo/day/year) 11/29/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 12/15/94 under the business name of GeoCore Services, Inc. by (signature) <i>Paul A. Kell</i>
--