

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Saline	SW 1/4 NE 1/4 NW 1/4	13	T 14 S	R 3 W E/W

Distance and direction from nearest town or city street address of well if located within city?

307 E. Walnut St. Salina, KS

2 WATER WELL OWNER:	This & That Lamps & Shades	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	618 E. Republic	Application Number:
City, State, ZIP Code :	Salina, Kansas 67401	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 1225
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 31.5 ft. below land surface measured on mo/day/yr 11/29/94
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield NA gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 8 in. to 40 ft., and in. to ft.
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes.....No..... X ...; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 2 in. to 25 ft., Dia. in. to ft., Dia. in. to ft.			Threaded. X
Casing height above land surface 3 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 25 ft. to 40 ft., From ft. to ft.		
GRAVEL PACK INTERVALS:	From 23 ft. to 40 ft., From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 21 ft., From 21 ft. to 23 ft., From ft. to ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				UST

Direction from well?	South	How many feet?	10		
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Concrete,			MW8
0.5	1	Sand,			GeoCore # 114118 Flush-mount Cover
1	4	Clay, Dark Brown			KDHE # 05085854 Tag # 00111825
4	7	Clay, Light Yellow to Brown			
7	11	Clay, Medium Brown			
11	15	Clay, Dark to Gray Brown			
15	20	Clay, Dark to Gray Brown			
20	24	Clay, Medium Gray			
24	26	Clay, Light Yellow Brown, Slight Orange			
26	31	Silt, Light Yellow Brown, Slight Orange			
31	34	Sand, Medium Gray			
34	40	Sand, Dark Gray			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/29/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 12/15/94 under the business name of GeoCore Services, Inc. by (signature) <i>Dale A. Bell</i>
