

1 LOCATION OF WATER WELL:		Fraction SW ¼ NW ¼ SW ¼	Section Number 24	Township Number T 14 S	Range Number R 3 W E/W
County: Saline Distance and direction from nearest town or city street address of well if located within city? 190' N of the NE corner of Jewell/Highland Ave					
2 WATER WELL OWNER: Payne Oil Co. RR#, St. Address, Box # : P.O. Box 671 City, State, ZIP Code : Salina, Kansas 67402		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL . 35 ft. ELEVATION: 1234 Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 1262.6 ^{29.6} ft. below land surface measured on mo/day/yr 3/15/95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield NA gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter . 8 .in. to . 35 .ft., and .in. to .ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only ① Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) ② PVC 4 ABS Blank casing diameter . 2 .in. to . 20 .ft., Dia .in. to .ft., Dia .in. to .ft. Casing height above land surface . 0 .in., weight lbs./ft. Wall thickness or gauge No. Sch. 40		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded X			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass ⑦ PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot ③ Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From . 20 .ft. to . 35 .ft., From .ft. to .ft.					
GRAVEL PACK INTERVALS: From . 18 .ft. to . 35 .ft., From .ft. to .ft.					
6 GROUT MATERIAL: 1 Neat cement ② Cement grout ③ Bentonite 4 Other Grout Intervals: From . 0 .ft. to . 16 .ft., From . 16 .ft. to . 18 .ft., From .ft. to .ft.					
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage ⑩ Other (specify below) UST Basin					
Direction from well? SW FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0	1	Clay, Dark Brown	MW10		
1	3	Clay, Dark Brown	GeoCore # 108	Flush-mount Cover	
3	10	Silt, Light Orange-Brown	KDHE # 05085862	Tag # 118222	
10	14	Clay, Medium Brown			
14	21	Silt, Light Orange-Brown			
21	25	Sand, Light Orange Brown			
25	32	Clay, Medium Brown w/slight orange tint			
32	35	Sand, Light Orange-Brown			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/15/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 4/95 under the business name of GeoCore Services, Inc. by (signature) Dale Robt					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					