		TER WELL RECORD FO	orm WWC-5	KSA 82a		
LOCATION OF WATE	R WELL: Fraction			on Number	Township Number	Range Number
County: SA/IÀ	ie Ne		) 1/4	36	T 14 (S	I R 3 RW
Distance and direction fr	om nearest town or city stree		within city?			i
27	17 Highla	nd		1		
WATER WELL OWN		V. Keopro	७७७७ १	-h		
RR#, St. Address, Box	#:  ̄ユス、!フ ト	tightand,		,	<del>-</del>	ure, Division of Water Resources
City, State, ZIP Code	· JAINA	7 5 - 9	0470		Application Numb	
LOCATE WELL'S LO	CATION WITH 4 DEPTH OF	COMPLETED WELL	53	. ft. ELEVA	TION: 12.5.	5
AN "X" IN SECTION	BOX: Depth(s) Grou	undwater Encountered 1	21.	ft. 2		ft. 3
	WELL'S STA	TIC WATER LEVEL 21	ft. be	low land sur	face measured on mo/da	ay/yr .3~3.1.¬.73
	Pi	ump test data: Well water	was3	2 ft. a	ter <b>/</b> hour	s pumping gpm
NW -	Est. Yield	LO. apm; Well water	was	ft. a	ter hour	s pumping gpm
	Bore Hole Dia	ameter	37	ft., a	and5.1/2	.in. to <b>53</b> ft.
* × ×:		R TO BE USED AS: 5	Public water	supply	8 Air conditioning	11 Injection well
	1 Domes				9 Dewatering	
sw	2 Irrigation					
	Was a chemic	cal/bacteriological sample sul	mitted to De			f yes, mo/day/yr sample was sub-
\$	mitted			Wa	ter Well Disinfected? Ye	
TYPE OF BLANK CA	ASING USED:	5 Wrought iron	8 Concre	te tile	CASING JOINTS:	Glued . 💢 Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (	specify below	v)	Welded
<b>@</b> PVC	4 ABS	7 Fiberglass				Threaded
Blank casing diameter .		ft., Dia	in. to		ft., Dia	in. to 1 ft.
Casing height above lan	nd surface	in., weight			ft. Wall thickness or gau	ge No. 5.D.R.26
TYPE OF SCREEN OR	PERFORATION MATERIAL:		<b>7</b> V		10 Asbestos-	cement
1 Steel	3 Stainless steel	5 Fiberglass	8 RM	P (SR)	` '	ecify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	3	12 None use	
SCREEN OR PERFORA	ATION OPENINGS ARE:	5 Gauzed	wrapped		8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wr	apped		9 Drilled holes	
2 Louvered shutte	r ' 4 Key punched	7 Torch c	ut _ >		10 Other (specify)	
SCREEN-PERFORATE	OINTERVALS: From	<b>で.</b> ふ	. S	ft., Froi	n	ft. to
	From					ft. toft.
GRAVEL PAC	K INTERVALS: From	<b>2.1</b> ft. to	<b>5</b> .3			ft. toft.
1	From	ft. to		ft., Fro		ft. to ft.
GROUT MATERIAL:		2 Cement grout	3 Bentor		•••••	
	_	•	ft. t			ft. to
	rce of possible contamination				•	14 Abandoned water well
-	4 Lateral lines	7 Pit privy			storage	
2 Sewer lines	5 Cess pool	8 Sewage lagoo	n		•	16 Other (specify below)
	r lines 6 Seepage pi	9 Feedyard			ticide storage	- 116/ GT
Direction from well?	LITHOLOG	4 E as [	FROM	How mai	ny feet?	NG INTERVALS
FROM, TO	E'II DIAT	The Ocall	PHOIN	-10	1 20001	NO INTERIORES
	_ ru pirt	+1007011				
4- 29'	Colar - RI	of uwor				
	10 1 = B	mal Al				
- 0 / - 1	Jyn p	7.0070				
391371	Class > 60	rev to				
		E 4 10				
	cark or	er-				
37101	MODE	sand and				
2/ 33	menon,	and and				
	Gravel					
						d under my indediction and rese
						d under my jurisdiction and was
completed on (mo/day/y	· · · · · · · · · · · · · · · · · · ·					ny knowledge and belief. Kansas
Water Well Contractor's	044	This Water Wel			/ \/	, Aub O
under the business nam			vice	by (signa		en Janey
INSTRUCTIONS: Use type	ewriter or ball point pen. <u>PLEASE PRE</u> nt, Bureau of Water, Topeka, Kansas (	SS FIRMLY and PRINT clearly. Pleas	e fill in blanks, u	nderline or circle	the correct answers. Send top WNER and retain one for your	three copies to Kansas Department records.
of Health and Environme	nii, bureau or water, ropeka, kansas (	00020-0001. Telephone: 913-290-334	o. oena one to:			