

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Saline		NE 1/4 NE 1/4 SE 1/4		27		T 14 S		R 3 W E/W	
Distance and direction from nearest town or city street address of well if located within city?									
315' E of Centennial Road									
2 WATER WELL OWNER:		L & S Construction Company							
RR#, St. Address, Box # :		2141 Centennial Rd.				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Salina, Kansas 67401				Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 20 ft. ELEVATION: 1241							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 12.3 ft. below land surface measured on mo/day/yr 3/29/95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield NA gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 20 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only (1) Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No. X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X							
		5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded (2) PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 10 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface -4.7 in. weight lbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: (7) PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot (3) Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 8 ft. to 20 ft. From ft. to ft. From ft. to ft. From ft. to ft.							
		6 GROUT MATERIAL: 1 Neat cement (2) Cement grout (3) Bentonite 4 Other Grout Intervals: From 0 ft. to 6 ft. From 6 ft. to 8 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage (16) Other (specify below) UST Basin 13 Insecticide storage Direction from well? NW How many feet? 10							
		FROM TO LITHOLOGIC LOG 0 0.5 Sand, 0.5 6 Clay, Medium Gray 6 9 Clay, Light Gray 9 15 Clay, Medium Brown 15 20 Clay, Medium Orange-Brown				FROM TO PLUGGING INTERVALS MW1 GeoCore # 103 Flush-mount Cover KDHE # 05085495 Tag # 117793			
		7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/29/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 4/11/95 under the business name of GeoCore Services, Inc. by (signature) <i>Roh Kohl</i>							