

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SALINE		NE 1/4 NE 1/4 NE 1/4	11	T 14 S	R 3 EW
Distance and direction from nearest town or city street address of well if located within city? 845 N. BROADWAY SALINE, KS.					
2 WATER WELL OWNER: TOWN & COUNTRY MARKETS					
RR#, St. Address, Box #: P.O. BOX 17087					
City, State, ZIP Code: WICHITA, KS. 67217					
Board of Agriculture, Division of Water Resources					
Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION: 1220.17			
		Depth(s) Groundwater Encountered 1. 24.5 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 21.38 ft. below land surface measured on mo/day/yr 3/27/95			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8.5 in. to 30 ft., and in. to ft.			
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <input checked="" type="radio"/> Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped <input checked="" type="radio"/> PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 15 ft. Dia. in. to ft. Dia. in. to ft. Casing height below land surface 58' weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot <input checked="" type="radio"/> 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 15 ft. to 30 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 13 ft. to 30 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement <input checked="" type="radio"/> 2 Cement grout <input checked="" type="radio"/> 3 Bentonite 4 Other					
Grout Intervals: From 1 ft. to 17 ft., From 11 ft. to 13 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy <input checked="" type="radio"/> 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon <input checked="" type="radio"/> 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? WEST How many feet? 80					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	TOPSOIL			
1	12.5	SILTY CLAY			
12.5	18.5	SILT			
18.5	30	SILTY CLAY			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <input checked="" type="radio"/> (1) constructed, <input type="radio"/> (2) reconstructed, or <input type="radio"/> (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/23/95 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 568 This Water Well Record was completed on (mo/day/yr) 5/17/95					
under the business name of MAX'S ENTERPRISES by (signature) David H. Hersh					