


1 LOCATION OF WATER WELL: County: Logan Fraction SW 1/4 SE 1/4 SW 1/4 Section Number 11 Township Number T 14 S Range Number R 32 EW

Distance and direction from nearest town or city street address of well if located within city?  
 XX 18 Miles South of Oakley, Ks.

2 WATER WELL OWNER: Randy Rose  
 RR#, St. Address, Box #: HC 2, Box 15A Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Russell Springs, Ks. 67755 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 60' ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 32' ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL: 32' ft. below land surface measured on mo/day/yr  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter: 10" in. to 60' ft., and in. to ft.  
 WELL WATER TO BE USED AS:  
 XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No XX; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes XX No

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XX Clamped  
 XX2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded  
 Blank casing diameter 5" in. to 40' ft., Dia. in. to ft., Dia. in. to ft.  
 Casing height above land surface 24" in., weight lbs./ft. Wall thickness or gauge No. SCH 40  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass XX PVC 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)  
 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot XX Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 40' ft. to 60' ft., From ft. to ft.  
 GRAVEL PACK INTERVALS: From 20' ft. to 60' ft., From ft. to ft.  
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout XX Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 20' ft., From ft. to ft., From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage XX Other (specify below)  
 13 Insecticide storage Old Windmill  
 Direction from well? 1/2 mile South How many feet? Plugged & Sealed

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top Soil			
2	14	Yellow Sandy Clay			
14	34	Black Silty Clay			
34	35	Coarse Sand			
35	60	Blue Shale			
	60	Total Depth of Well			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was XX constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-27-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. #514 This Water Well Record was completed on (mo/day/yr) 01-04-90 under the business name of Miller Gearhead & Pump Repair Inc. by (signature) *Wendy Miller*

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY  
T  
R  
EW  
SEC.  
1/4  
1/4  
1/4