

CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

County: Wallace

Location listed as:

Section-Township-Range: 34-14S-49W

Fraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): SW SE SE

Location changed to:

34-14S-39W

SW SE SE

Other changes: Initial statements: _____

Changed to: _____

Comments: _____


verification method: Wallace County Map

initials: JB date: 9-27-04

1 LOCATION OF WATER WELL: County: Wallace Fraction: SW 1/4 SE 1/4 SE 1/4 Section Number: 34 Township Number: T 14 S Range Number: R 49 E/W

Distance and direction from nearest town or city street address of well if located within city? 8 S 6 E Sharon Springs GPS UTM 14S 0 271150 4296173

2 WATER WELL OWNER: Ray Smith
 RR#, St. Address, Box #: 693 Ks 27
 City, State, ZIP Code: Sharon Springs Ks. 67758
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 182 ft. ELEVATION: 3590
 Depth(s) Groundwater Encountered: 1 162 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL: 162 ft. below land surface measured on mo/day/yr 8-13-04
 Pump test data: Well water was 165 ft. after hours pumping gpm
 Est. Yield 302 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded
 Blank casing diameter 6 5/8 steel in. to 5 ft. Dia 5 1/2 PVC in. to 160 ft. Dia in. to ft.
 Casing height above land surface 2 in., weight 168 steel 265 PVC lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 160 ft. to 183 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 30 ft. to 183 ft., From ft. to ft.

6 GROUT MATERIAL: Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 5 ft. to 30 ft., From ft. to ft.
 What is the nearest source of possible contamination:
 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? NE How many feet? 200

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	20	clay			
20	40	limestone			
40	60	sand			
60	75	sandy clay			
75	90	sand			
90	96	cemented sand			
96	150	sandy clay			
150	175	sand & gravel			
175	180	o.g. clay			
180	183	shale			

RECEIVED
 AUG 30 2004

BUREAU OF WATER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-15-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 213 This Water Well Record was completed on (mo/day/yr) 8-25-04 under the business name of Kemp's Well Service by (signature) George Kemp