USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## SOUTH FLATS

WATER WELL RECORD A (12) KSA 82a-1201-1215

Kansas Department of Health and **Environment-Division of Environment** (Water well Contractors) Topeka, Kansas 66620

1. Location of well:	County	Lace   West to a vaf   NE 1/4 SW 1/4 NE 1/4   19		Section number		Township number	Range number	
	Wallace			19		T 14 s	r 39	EÆ
2 miles east of Chamen Chaines				3. Owner of well: Don Hoover R.R. or street:				
Street address of well i	location it in city:		City, st	ate, zip	code: S	haron Springs,	Kansas	
4. Locate with "X" in section below:  N						6. Bore hole dia. 30 in. Completion date 4-25-17 Well depth 201 ft.		
center of $\mathbf{N}$ $SW_{ij}^{1}$ $NE_{ij}^{1}$ Se				er 10		7 Cable tool Rotary Driven Dug Hollow rod Jetted Bored X Reverse rotary		
- W	Two 5	4, Rge 39	2		976 	8. Use: Domestic Public supply Industry X Ignigation Air conditioning Stock		
sw	SE	in the second se	v				il field water Ot	
<u> </u>	27.17	L. W. D. W. C. W.			erionen i propone	P. Casing; Material Steel Height: Above or below Threaded Welded X Surface 12 in.  RMP PVC Weight 36 lbs./ft.		
s I <del>⊸</del> 1 Mile		A Committee of the Comm		}		Dia.16 in. +201 ft. dep		
5. Type and color of m	naterial		the designation of the	From	То	Dia in. to ft. dep	th gage No. <u>-21</u> 0	9
clay sand rock				0	123.	Johnson Type Steel Dig. 16"		
medium sand			123	130	Slot/gauze 2" Set between 151	Length 50 t ft. and 201	ft.	
clay and rock				130	140	Gravel pack? <u>YES</u> Size ra		Bft.
sandy clay and rock				140	154	11. Static water level:  119 ft. below land sur	face Date 4-25	/day/yr. - 77
medium to good fairly loose clean				154	193	12. Rymping level below land surfaces:  130 ft. after 2 hrs. pumping 1280 g.p.m.  184 ft. after 5 hrs. pumping g.p.m.  Estimated maximum yield 1280 g.p.m.		
soapstone				193	201			
	BROO	( 193'				13. Water sample submitted:		/day/yr.
	•					14. Well head completion:		
						X Pitless adapter	12 Inches above s	rade
				<del> </del>	$\vdash \vdash \vdash$	15. Well grouted?		
						With: X Neat cement ft. to	— gentonite —— C	oncrete _
						16. Nearest source of possible	contamination: no	
						Well disinfected upon comple	.///	No
						17. Pump:  Manufacturer's name JO	Not installed	
							HP $80$ Volt $\Omega$ ft. capacity $500$	
						Type: Submersible	X Turbine	
(Use a second sheet if needed)						Jet Centrifugal	Reciprod	cating
18. Elevation: 1	Elevation: 19. Remarks:					20. Water well contractor's of This well was drilled under m		
3546 (Turu)						is true to the best of my know	ledge and belief.	
Topography:					ļ	Northwest Drill		
	X Slope					Business name	11	nse No.
— Hill						Address — Coodla		