

## WATER WELL RECORD Form WWC-5 KSA 82a-1212

LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Saline</u>	<u>SE 1/4 SE 1/4 NW 1/4</u>	<u>26</u>	T <u>14</u> S	R <u>4</u> E/W

Distance and direction from nearest town or city street address of well if located within city?

Approximately 4 miles west of Salina on 140WATER WELL OWNER: Darrell HillRR#, St. Address, Box # : 1 DMH LaneCity, State, ZIP Code : Salina, KS 67401

Board of Agriculture, Division of Water Resources

Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

DEPTH OF COMPLETED WELL: 77 ft. ELEVATION:Depth(s) Groundwater Encountered 1. 40 ft. 2. ft. 3. ft.WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 10 gpm: Well water was ft. after hours pumping gpmBore Hole Diameter: 10 in. to 82 ft., and 4.5 in. to 101 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

① Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No ☒

TYPE OF BLANK CASING USED:

5 Wrought iron

8 Concrete tile

CASING JOINTS: Glued ☒ Clamped

1 Steel

3 RMP (SR)

6 Asbestos-Cement

9 Other (specify below)

Welded

② PVC

4 ABS

7 Fiberglass

Threaded ☒Blank casing diameter 6 in. to 22 ft., Dia 6 in. to 67 ft., DiaCasing height above land surface 30 in., weight lbs./ft. Wall thickness or gauge No. 160

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless steel

5 Fiberglass

⑦ PVC

10 Asbestos-cement

2 Brass

4 Galvanized steel

6 Concrete tile

8 RMP (SR)

11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

③ Mill slot .025"

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

7 Torch cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 22 ft. to 32 ft., From 67 ft. to 77 ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 18 ft. to 101 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GROUT MATERIAL:

1 Neat cement

2 Cement grout

③ Bentonite

4 Other

Grout Intervals: From 2 ft. to 18 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well?

How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	12	Brown Clay, silty, soft			
12	23	Lt. Red Brown Clay, silty, soft			
23	33	Gravel, med. to coarse w/ a trace of sand and clay, drilled v. well			
33	37	Brown Clay, silty, soft			
37	43	Silt, clayey w/ occasional fine sand			
43	45	Sand, w/ trace of gravel, clayey			
45	51	Clay, sandy, silty			
51	67	Shale, gray, soft			
67	71	Gravel, med. to coarse, w/ occ. sand good porosity			
71	78	Shale, gray			
78	82	Shale, gray w/ sand and gravel			
82	99	Shale, interbedded gray and maroon			
99	101	Shale, red w/ white anhydrite (Permian)			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/8/97 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 8/11/97Under the business name of GeoCore Services, Inc. by (signature) Dan A. Kott