


1 LOCATION OF WATER WELL: County: Saline	Fraction NW 1/4 NE 1/4 SE 1/4	Section Number 35	Township Number T 14 S	Range Number R 4 E/W	
Distance and direction from nearest town or city street address of well if located within city? 2 miles East & 1/2 mile South of Bavaria, Ks.					
2 WATER WELL OWNER: Darrel Hills RR#, St. Address, Box # : 2129 W. Humbargar Rd. City, State, ZIP Code : Salina, Ks. 67401 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 174 ft. ELEVATION: Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 62 ft. below land surface measured on mo/day/yr 1/31/06 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering X2 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well stock Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X PVC 4 ABS 7 Fiberglass Welded Blank casing diameter 5 in. to 1.34 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 24 in., weight 2.37 lbs./ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass X PVC 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify) 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 5 Guazed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter X Mill slot 6 Wire wrapped 9 Drilled holes 4 Key punched 7 Torch cut 10 Other (specify) ft. SCREEN-PERFORATED INTERVALS: From 1.34 ft. to 174 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 174 ft., From ft. to ft. From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout X Bentonite 4 Other Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: None within 1/4 mile 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil			
2	14	Clay, brown			
14	20	Sandstone, dark tan			
20	26	Clay, dark brown			
26	40	Sandstone, tan			
40	52	Shale, light gray			
52	66	Sandstone, light gray			
66	132	Shale, fractured, gray/sandstone light gray			
132	174	Fractured shale, gray			
174	180	Shale, gray			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was **X** constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **1/31/06** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No **138** This Water Well Record was completed on (mo/day/yr) **2/8/06** under the business name of **Peterson Irrigation, Inc.** by (signature) *Mike Peterso*