

LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Saline	SW ¼ SE ¼ SE ¼	28	T 14 S	R 4 W

Distance and direction from nearest town or city street address of well if located within city?

1/2 mile West of Bavaria, KS

WATER WELL OWNER:	Rex Blood	
RR#, St. Address, Box # :	7357 W. Magnolia Rd.	Board of Agriculture, Division of Water Resources
City, State, ZIP Code :	Salina, KS 67401	Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N	
--- NW ---	--- NE ---
W	
--- SW ---	--- SE ---
S	

1 Mile

4. DEPTH OF COMPLETED WELL. 47 ft. ELEVATION. 11 ft.

Depth(s) Groundwater Encountered 11 ft. 11 ft. 3. 11 ft.

WELL'S STATIC WATER LEVEL 11 ft. below land surface measured on mo/day/yr 6-13-89

Pump test data: Well water was 15-30 gpm: Well water was 22 ft. after 1 1/2 hours pumping 12 gpm

Est. Yield 8 in. to 47 ft., and 12 in. to 12 ft.

Bore Hole Diameter 8 in. to 47 ft., and 12 in. to 12 ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	9 Dewatering
	7 Lawn and garden only	10 Monitoring well

12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X....; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued	Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded	
2 PVC	4 ABS	7 Fiberglass		Threaded	
Blank casing diameter 5 in. to 38 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 12 in., weight 2.91 lbs./ft. Wall thickness or gauge No. 265					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC	10 Asbestos-cement		
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)	
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes		
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)		
SCREEN-PERFORATED INTERVALS:		From 38 ft. to 47 ft., From ft. to ft.			
		From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS:		From 20 ft. to 47 ft., From ft. to ft.			
		From ft. to ft., From ft. to ft.			

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? East How many feet? 80

[illegible]

7. CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-13-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 6-15-89 under the business name of Peterson Irrigation, Inc. by (signature) Mike Peterson