

LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SALINE		SE ¼ SE ¼ SE ¼	13	T 14 S	R 4 E/W
Distance and direction from nearest town or city street address of well if located within city? 4860 W. CRAWFORD					
WATER WELL OWNER: ELIZABETH AND CHARLES SCHNEIDER RR#, St. Address, Box # : 2548 S. LIGHTVILLE RD. City, State, ZIP Code : SALINA, KS. 67401					
Board of Agriculture, Division of Water Resources Application Number:					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;">N --- NW --- NE --- --- SW --- SE --- S</div>		DEPTH OF COMPLETED WELL... 49.8 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 19 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 19 ft. below land surface measured on mo/day/yr 10-8-94 Pump test data: Well water was 44 ft. after 4 hours pumping 25 gpm Est. Yield 30 gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 60 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter 5 in. to 40 ft., Dia 160 in. to ft., Dia in. to ft. Casing height above land surface 22 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 26		CASING JOINTS: Glued X Clamped Welded Threaded 5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot .035 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 40 ft. to 49.8 ft.		GRAVEL PACK INTERVALS: From 25 ft. to 49.8 ft.			
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From 3 ft. to 25 ft. From ft. to ft. From ft. to ft.			
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? SOUTH How many feet? 80					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0 2 TOP SOIL					
2 38 CLAY SILTY TAN					
38 45 CREEK GRAVEL BROWN SANDY					
45 49.8 CLAY LIGHT GRAY SOFT					
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-8-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 388 This Water Well Record was completed on (mo/day/yr) 10-8-94 by (signature) PESTINGER PUMP SERVICE					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					