

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

DBA

1. Location of well: <u>Wallace</u>		County: <u>Wallace</u>	Fraction: <u>NE 1/4 NW 1/4 SE 1/4</u>	Section number: <u>29</u>	Township number: <u>T 14</u>	Range number: <u>S R 40</u>	<u>EW</u>																																																																																																																																												
2. Distance and direction from nearest town or city: <u>SHARON SPRING</u> Street address of well location in city: <u>55 1/2 W 1/2 S 1/4 W</u>				3. Owner of well: <u>John Klinge</u> R.R. or street: City, state, zip code: <u>Sharon Springs Kan 67758</u>																																																																																																																																															
4. Locate with "X" in section below: N W E S 1 Mile			Sketch map:		6. Bore hole dia. <u>3 1/2</u> in. Completion date <u>10-12-78</u> Well depth <u>257</u> ft.																																																																																																																																														
			<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th style="width:50%;">5. Type and color of material</th> <th style="width:10%;">From</th> <th style="width:10%;">To</th> </tr> <tr> <td><u>Top Soil</u></td> <td><u>0</u></td> <td><u>4</u></td> </tr> <tr> <td><u>Clay</u></td> <td><u>4</u></td> <td><u>31</u></td> </tr> <tr> <td><u>Sandy Clay, Gravel</u></td> <td><u>31</u></td> <td><u>101</u></td> </tr> <tr> <td><u>Fine Sand, Clay</u></td> <td><u>101</u></td> <td><u>127</u></td> </tr> <tr> <td><u>M Gravel</u></td> <td><u>127</u></td> <td><u>141</u></td> </tr> <tr> <td><u>Fine Sand, Sandstone</u></td> <td><u>141</u></td> <td><u>175</u></td> </tr> <tr> <td><u>M Gravel</u></td> <td><u>175</u></td> <td><u>189</u></td> </tr> <tr> <td><u>Sandy Clay, Sandstone</u></td> <td><u>189</u></td> <td><u>201</u></td> </tr> <tr> <td><u>M Gravel</u></td> <td><u>201</u></td> <td><u>237</u></td> </tr> <tr> <td><u>Sandy Clay</u></td> <td><u>237</u></td> <td><u>239</u></td> </tr> <tr> <td><u>M Gravel</u></td> <td><u>239</u></td> <td><u>242</u></td> </tr> <tr> <td><u>Ochre</u></td> <td><u>242</u></td> <td><u>257</u></td> </tr> <tr> <td colspan="3" style="text-align:center;"><u>BROCK 242'</u></td> <td colspan="2"></td> <td colspan="3">7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary</td> </tr> <tr> <td colspan="3"></td> <td colspan="2"></td> <td colspan="3">8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other</td> </tr> <tr> <td colspan="3"></td> <td colspan="2"></td> <td colspan="3">9. Casing: Material <u>Steel</u> Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface <u>12</u> in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight <u>36</u> lbs./ft. Dia. <u>16</u> in. to <u>194</u> ft. depth Wall Thickness, inches or Dia. <u> </u> in. to <u> </u> ft. depth gage No. <u>219</u></td> </tr> <tr> <td colspan="3"></td> <td colspan="2"></td> <td colspan="3">10. Screen: Manufacturer's name <u>W. H. Brown</u> Type <u>Louyer</u> Dia. <u>16</u> Slot/gauze <u>1/8</u> .219 Length <u>60</u> Set between <u>194</u> ft. and <u>257</u> ft. Gravel pack? <u>Yes</u> Size range of material <u>1/4" # 20</u></td> </tr> <tr> <td colspan="3"></td> <td colspan="2"></td> <td colspan="3">11. Static water level: <u>147</u> ft. below land surface Date <u>9-28-78</u> mo./day/yr.</td> </tr> <tr> <td colspan="3"></td> <td colspan="2"></td> <td colspan="3">12. Pumping level below land surfaces: <u>270</u> ft. after <u>3</u> hrs. pumping <u>1400</u> g.p.m. <u> </u> ft. after <u> </u> hrs. pumping <u> </u> g.p.m. Estimated maximum yield <u>1500</u> g.p.m.</td> </tr> <tr> <td colspan="3"></td> <td colspan="2"></td> <td colspan="3">13. Water sample submitted: <u> </u> mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <u> </u></td> </tr> <tr> <td colspan="3"></td> <td colspan="2"></td> <td colspan="3">14. Well head completion: <input type="checkbox"/> Pitless adapter <u> </u> Inches above grade</td> </tr> <tr> <td colspan="3"></td> <td colspan="2"></td> <td colspan="3">15. Well grouted? <u>Yes</u> With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From <u>0</u> ft. to <u>10</u> ft.</td> </tr> <tr> <td colspan="3"></td> <td colspan="2"></td> <td colspan="3">16. Nearest source of possible contamination: ft. <u> </u> Direction <u> </u> Type <u>None</u> Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No</td> </tr> <tr> <td colspan="3"></td> <td colspan="2"></td> <td colspan="3">17. Pump: <u> </u> Not installed Manufacturer's name <u>Western Land Rullen</u> Model number <u>8M</u> HP <u>100</u> Volts <u> </u> Length of drop pipe <u>240</u> ft. capacity <u>1200</u> g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other</td> </tr> <tr> <td colspan="3">18. Elevation:</td> <td colspan="2">19. Remarks:</td> <td colspan="3">20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>Keith Duffing to be 166</u> Business name <u> </u> License No. <u> </u> Address <u> </u> Signed <u>Beil Clifford</u> Date <u>10-13-78</u> Authorized representative</td> </tr> <tr> <td colspan="3">Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley</td> <td colspan="2"></td> <td colspan="3"></td> </tr> </table>		5. Type and color of material	From	To	<u>Top Soil</u>	<u>0</u>	<u>4</u>	<u>Clay</u>	<u>4</u>	<u>31</u>	<u>Sandy Clay, Gravel</u>	<u>31</u>	<u>101</u>	<u>Fine Sand, Clay</u>	<u>101</u>	<u>127</u>	<u>M Gravel</u>	<u>127</u>	<u>141</u>	<u>Fine Sand, Sandstone</u>	<u>141</u>	<u>175</u>	<u>M Gravel</u>	<u>175</u>	<u>189</u>	<u>Sandy Clay, Sandstone</u>	<u>189</u>	<u>201</u>	<u>M Gravel</u>	<u>201</u>	<u>237</u>	<u>Sandy Clay</u>	<u>237</u>	<u>239</u>	<u>M Gravel</u>	<u>239</u>	<u>242</u>	<u>Ochre</u>	<u>242</u>	<u>257</u>	<u>BROCK 242'</u>					7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary								8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other								9. Casing: Material <u>Steel</u> Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface <u>12</u> in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight <u>36</u> lbs./ft. Dia. <u>16</u> in. to <u>194</u> ft. depth Wall Thickness, inches or Dia. <u> </u> in. to <u> </u> ft. depth gage No. <u>219</u>								10. Screen: Manufacturer's name <u>W. H. Brown</u> Type <u>Louyer</u> Dia. <u>16</u> Slot/gauze <u>1/8</u> .219 Length <u>60</u> Set between <u>194</u> ft. and <u>257</u> ft. Gravel pack? <u>Yes</u> Size range of material <u>1/4" # 20</u>								11. Static water level: <u>147</u> ft. below land surface Date <u>9-28-78</u> mo./day/yr.								12. Pumping level below land surfaces: <u>270</u> ft. after <u>3</u> hrs. pumping <u>1400</u> g.p.m. <u> </u> ft. after <u> </u> hrs. pumping <u> </u> g.p.m. Estimated maximum yield <u>1500</u> g.p.m.								13. Water sample submitted: <u> </u> mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <u> </u>								14. Well head completion: <input type="checkbox"/> Pitless adapter <u> </u> Inches above grade								15. Well grouted? <u>Yes</u> With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From <u>0</u> ft. to <u>10</u> ft.								16. Nearest source of possible contamination: ft. <u> </u> Direction <u> </u> Type <u>None</u> Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No								17. Pump: <u> </u> Not installed Manufacturer's name <u>Western Land Rullen</u> Model number <u>8M</u> HP <u>100</u> Volts <u> </u> Length of drop pipe <u>240</u> ft. capacity <u>1200</u> g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other			18. Elevation:			19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>Keith Duffing to be 166</u> Business name <u> </u> License No. <u> </u> Address <u> </u> Signed <u>Beil Clifford</u> Date <u>10-13-78</u> Authorized representative			Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley							
					5. Type and color of material	From	To																																																																																																																																												
<u>Top Soil</u>	<u>0</u>	<u>4</u>																																																																																																																																																	
<u>Clay</u>	<u>4</u>	<u>31</u>																																																																																																																																																	
<u>Sandy Clay, Gravel</u>	<u>31</u>	<u>101</u>																																																																																																																																																	
<u>Fine Sand, Clay</u>	<u>101</u>	<u>127</u>																																																																																																																																																	
<u>M Gravel</u>	<u>127</u>	<u>141</u>																																																																																																																																																	
<u>Fine Sand, Sandstone</u>	<u>141</u>	<u>175</u>																																																																																																																																																	
<u>M Gravel</u>	<u>175</u>	<u>189</u>																																																																																																																																																	
<u>Sandy Clay, Sandstone</u>	<u>189</u>	<u>201</u>																																																																																																																																																	
<u>M Gravel</u>	<u>201</u>	<u>237</u>																																																																																																																																																	
<u>Sandy Clay</u>	<u>237</u>	<u>239</u>																																																																																																																																																	
<u>M Gravel</u>	<u>239</u>	<u>242</u>																																																																																																																																																	
<u>Ochre</u>	<u>242</u>	<u>257</u>																																																																																																																																																	
<u>BROCK 242'</u>					7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary																																																																																																																																														
					8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other																																																																																																																																														
					9. Casing: Material <u>Steel</u> Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface <u>12</u> in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight <u>36</u> lbs./ft. Dia. <u>16</u> in. to <u>194</u> ft. depth Wall Thickness, inches or Dia. <u> </u> in. to <u> </u> ft. depth gage No. <u>219</u>																																																																																																																																														
					10. Screen: Manufacturer's name <u>W. H. Brown</u> Type <u>Louyer</u> Dia. <u>16</u> Slot/gauze <u>1/8</u> .219 Length <u>60</u> Set between <u>194</u> ft. and <u>257</u> ft. Gravel pack? <u>Yes</u> Size range of material <u>1/4" # 20</u>																																																																																																																																														
					11. Static water level: <u>147</u> ft. below land surface Date <u>9-28-78</u> mo./day/yr.																																																																																																																																														
					12. Pumping level below land surfaces: <u>270</u> ft. after <u>3</u> hrs. pumping <u>1400</u> g.p.m. <u> </u> ft. after <u> </u> hrs. pumping <u> </u> g.p.m. Estimated maximum yield <u>1500</u> g.p.m.																																																																																																																																														
					13. Water sample submitted: <u> </u> mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <u> </u>																																																																																																																																														
					14. Well head completion: <input type="checkbox"/> Pitless adapter <u> </u> Inches above grade																																																																																																																																														
					15. Well grouted? <u>Yes</u> With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From <u>0</u> ft. to <u>10</u> ft.																																																																																																																																														
					16. Nearest source of possible contamination: ft. <u> </u> Direction <u> </u> Type <u>None</u> Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No																																																																																																																																														
					17. Pump: <u> </u> Not installed Manufacturer's name <u>Western Land Rullen</u> Model number <u>8M</u> HP <u>100</u> Volts <u> </u> Length of drop pipe <u>240</u> ft. capacity <u>1200</u> g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other																																																																																																																																														
18. Elevation:			19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>Keith Duffing to be 166</u> Business name <u> </u> License No. <u> </u> Address <u> </u> Signed <u>Beil Clifford</u> Date <u>10-13-78</u> Authorized representative																																																																																																																																														
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley																																																																																																																																																			

14
 40
 29
 NE NW SE
 1/4 1/4 1/4