USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

						•	• · · · · · · · · · · · · · · · · · · ·		
1. Location of well:	County	Fraction		Section	number	Township number	Range number		
	Wallace	NW 1/4 NW 1/4]		28		т 14 s	r · 41	/ /W	
l Sugger Springs					3. Owner of well: Vaughn Young				
7½ mi. West: 5½ mi. Northe Street address of well location if in city: City, state					treet: te, zip code: Tribune, KS 67879				
4. Locate with "X" in section below: Sketch map:						6. Bore hole dia. 30 in. Completion date			
N N						Well depth 235 ft. 6-29-78			
X						7 Cable tool X Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary			
						8. Use: Domestic Public supply Industry			
× ·	Exercise Control				•	X Irrigation Air conditioning Stock			
SW	SE					9. Casing: QMaterial Steel Height: Above or below			
[Threaded Welded X Surface 12 in. RMP by PVC Weight Ibs./ft.			
S 1 1 M	www.pater.com.com.com.com.com.com.com.com.com.com	And the second of the				Dia.16 in. to ft. dep			
5. Type and color of	material			From	То	Dia in. to ft. dep	th gage No188		
	the state of the s	The same of the sa	eranders in a Villa in the same of			10. Screen: Manufacturer's Cook - 225 -23	name		
Top Soil				- 0	52	TypeWite Wrapp	761		
Large To Medium Gravel & Gravel				52	60	Slot/gauze 10% Set between 165	_ Length <u>60 '</u> _ft. and <u>225</u>	ft.	
Small Sandy Clay Streaks				60	64	Perf. W A Brow Gravel pack? X Size ra			
						11. Static water level:		/day/yr. #	
Large to Med. Gravel				64	73	ft. below land sur	face Date <u>7-8-7</u>	78	
Sandy Clay				73		12. Pumping level below land 162 ft. after		a.p.m.	
Large to Med. Gravel				77	94	185 ft. after 2 hrs. pumping 1900 g.p.m.			
Sandy Clay with Traces of Sandstone				94	125	Estimated maximum yield			
Tamas Wall Council				105	100	Yes X No Date			
Large Med. Gravel					133	14. Well head completion: Pitless adapter 12 Inches above grade			
Sandy Clay & Small Med. Gravel					139	15. Well grouted? X		1	
Med. Gravel				139	151	1 With: Neat cement Bentonite X Concrete Depth: From Off. to 10 ft.			
Sandy Clay & Sandstone					154	16. Negrest source of possibl		IF	
						ft. 5000 Direction West Type Farmstead Well disinfected upon completion? Yes X No			
Large Med. Gravel				154	165	17. Pump:	X Not installed		
Sandy Clay - Sandstone				165	175	Manufacturer's name HP Volts			
Large Med. Gravel				175	196	Length of drop pipe		-	
Sandy Clay				196	198	Type: Submersible	Turbine	•	
Targe Med Crayel				198		Jet Reciprocating			
18. Elevation:	(Use a second s	heet if needed)	7	1 = 70	1205	Centrifugal 20. Water well contractor's	Other	— * K	
.57 210 (011)	P	ROCK (•			This well was drilled under m	y jurisdiction and this re	eport	
Topography:					is true to the best of my knowledge and belief. Western Well & Pump 245			ع ≥ <u>≥</u>	
— Hill						Business name		nea No	
Slope X Upland						Address P.U. BOX	Date 2	- 1 × 10	
Valley						Signed Outhorized rep	resentative Date 2	3 2 P	