

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

DCC

1. Location of well: County Wallace		Fraction SW 1/4 SW 1/4 SE 1/4		Section number 3		Township number T 14 S R 42 E/W	
2. Distance and direction from nearest town or city: 1 Mile S, 1 w, Weskan, Kansas Street address of well location if in city:				3. Owner of well: RWD # 1 R.R. or street: City, state, zip code: Weskan, Kansas			
4. Locate with "X" in section below: Sketch map: N 1 Mile W E S 1 Mile 50' E and 64' N of SW corner of the SE 1/4, Sec. 3, T14S, R42W, Wallace Co., Kansas X 1 Mile				6. Bore hole dia. 28 in. Completion date 9-3-76 Well depth 377 ft.			
5. Type and color of material				7. Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary			
				8. Use: <input type="checkbox"/> Domestic <input checked="" type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other			
From To				9. Casing: Material Stl Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 45 lbs./ft. Dia. 12 in. to 315 ft. depth Wall Thickness: inches or Dia. 12 in. to 317 ft. depth gauge No. .330			
				10. Screen: Manufacturer's name Doerr Type Louvered Dia. 12" Slot/gauze 1/8" Length 60 Set between 317 ft. and 377 ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 4.4 mm			
Top soil				11. Static water level: 169 ft. below land surface Date 4-30-76 mo./day/yr.			
Sandy tan clay				12. Pumping level below land surfaces: Not pumped ____ ft. after ____ hrs. pumping ____ g.p.m. ____ ft. after ____ hrs. pumping ____ g.p.m. Estimated maximum yield _____ g.p.m.			
Fine to coarse medium gravel				13. Water sample submitted: _____ mo./day/yr. Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Date _____			
Red tan clay with light gravel streaks				14. Well head completion: <input checked="" type="checkbox"/> Pitless adapter _____ Inches above grade			
Fine to coarse sand medium gravel with light clay				15. Well grouted? <input checked="" type="checkbox"/> With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 5 ft. to 20 ft.			
Red tan clay				16. Nearest source of possible contamination: unk ft. _____ Direction _____ Type _____ Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No			
Fine to coarse sand medium gravel with clay				17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Goulds Model number 6 IHC HP 30 Volts 400 Length of drop pipe 336 ft. capacity 200 g.p.m. Type: <input checked="" type="checkbox"/> Submersible _____ Turbine _____ Jet _____ Reciprocating _____ Centrifugal _____ Other			
Green clay				20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Layne-Western Co., Inc. 102 Business name License No. Address Garden City, Kansas Signed R.L. [Signature] Date 1 Dec 76 Authorized representative			
Tan clay with sand and gravel				18. Elevation: _____ 19. Remarks: BROCK 377 (Use a second sheet if needed)			
Fine to coarse sand medium gravel							
Fine to coarse sand medium gravel tan & green clay				21. Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley			
Black shale							

14 420 3 SW SE