


USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

BDD

1. Location of well:	County Wallace	Fraction Center of section SE 1/4 SE 1/4 NW 1/4	Section number 11	Township number T 14 S R 42 W E/W	Range number
2. Distance and direction from nearest town or city: 3/4 mile south, 1/2 mile East of Weskan, Kansas Street address of well location if in city:			3. Owner of well: Harold Johannas R.R. or street: City, state, zip code: Weskan, Kansas 67762		
4. Locate with "X" in section below: Sketch map:  Center X of Section 11, Twp. 14, Rge. 42 W			6. Bore hole dia. 30 in. Completion date 12-9-75 Well depth 380 ft.		
5. Type and color of material			7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
clay sandy clay and sand and rock streaks			8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
sandy clay			9. Casing: Material steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36 lbs./ft. Dia. 16 in. to 380 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 219		
medium sands loose and clean			10. Screen: Manufacturer's name W. A. Brown Type steel Dia. 16 Slot/gauze 2" Length 260 Set between 120 ft. and 380 ft. ft. and <input type="checkbox"/> ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 3/8		
clay and rock			11. Static water level: <input type="checkbox"/> mo./day/yr. 136 ft. below land surface Date 1-15-76		
medium to good loose and clean			12. Pumping level below land surfaces: 160 ft. after 5 hrs. pumping 1400 g.p.m. 172 ft. after 5 hrs. pumping 2000 g.p.m. Estimated maximum yield 2000 g.p.m.		
yellow-gray slip clay			13. Water sample submitted: <input type="checkbox"/> mo./day/yr. Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date		
sandy clay and rock			14. Well head completion: <input type="checkbox"/> Pitless adapter 12 inches above grade		
medium to good loose and clean			15. Well grouted? yes With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.		
clay and sandy clay			16. Nearest source of possible contamination: none ft. Direction Type Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No		
medium sands loose and clean			17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Gould Model number Turbine HP Volts Length of drop pipe 300 ft. capacity 1600 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
clay and rock			20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Northwest Drilling Co., Inc. Business name License No. Address Box 411, Goodland, Kansas Signed Ken Hays Date 7-12-76 Authorized representative		
medium sands loose and clean			18. Elevation:		
sandy clay			19. Remarks: Block 393'		
(Cont. on Page II) (Use a second sheet if needed)			Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley		

174 420 11
K
Sec

Harold Johannas (cont.)

Medium to good loose and clean clay and rock	295	305
	305	313
medium to good loose and clean hard rock and sticky slip clay	313	321
	321	333
clay and slip clay	333	355
medium sands loose and clean	355	359
medium to good loose and clean soapstone	359	373
	373	375
blue shale	375	380