USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WESKAN

WATER WELL RECORD
KSA 82a-1201-1215

CBA

T	R	EW	sec	1/4	1/4	1/4	No.

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County	Township name	Fraction	Section number	Town number	Range number
	Wallace		NE, NW, SW	22	T 14 S	R 42 W

Distance and direction from nearest town or city: Approx. 3 S. & 1 W. of Wes Kan
Street address of well location if in city:

3 Owner of well: Ed Waugh
Address: Wes Kan, Ks

Locate with "X" in section below: Sketch map:

N
W X E
S
1 Mile

4 Well depth: 410 ft. Date of completion
Well diameter 28 in. 23 Apr 75

5 ☐ Cable tool ☐ Rotary ☐ Driven ☐ Dug
☐ Hollow rod ☐ Jetted ☐ Bored ☒ Reverse rotary

6 Use: ☐ Domestic ☐ Public supply ☐ Industry
☒ Irrigation ☐ Air conditioning ☐ Commercial
☐ Test well ☐

7 Casing: Material steel Height: above/~~below~~
Threaded ☐ Welded ☒ Surface 12 in.
Diam. Weight 37 lbs./ft.
16 in. to 410 ft. depth Drive shoe? ☐ Yes ☒ No
in. to ft. depth

2

Type and color of material	From	To
Well drilled near the site of		
TH 5-75 (see attached), which		
is 420' S. & 760' E of the NW cor		
of SW ¼, Sec 22, 14-42, Wallace Co.		
All the casing was pulled from the		
abandoned well (referred to on the		
test hole log), and the hole was		
filled with natural earth materials.		
BROCK 410'		
(use a second sheet if needed)		

8 Screen:
Manufacturer W. A. Brown & L. B. Foster
Type Louver & Mill slot Diam. 16"
~~Slot/gauze~~ 1/8" Length 217'
Set between 193 ft. and 410 ft.
Fittings: 1-6 mm
Gravel pack ☒ Yes ☐ No Size range of material

9 Static water level:
145 ft. below land surface Date 4 Apr 75

10 Pumping level below land surfaces:
173 ft. after 1 hrs. pumping 2265 g.p.m.
185 ft. after 1 hrs. pumping 3000 g.p.m.
Estimated maximum yield 4000 g.p.m.

11 Water sample submitted:
☐ Yes ☒ No Date

12 Well head completion:
☐ Pitless adapter ☒ Inches above grade

13 Well grouted? ☒ Yes ☐ No
☐ Neat cement ☒ Bentonite ☐
Depth: From 0 ft. to 10 ft.

14 Nearest source of possible contamination: Unk
ft. Direction Type
Well disinfected upon completion? ☐ Yes ☐ No

15 Pump: ☐ Not installed
Manufacturer's name Layne
Model number 14TL HP 150 Volts
Length of drop pipe 240 ft. capacity 2250 g.m.p.
Type:
☐ Submersible ☒ Turbine
☐ Jet ☐ Reciprocating
☐ Certrifugal ☐ Other

16 Remarks: elevation 3829 (TOPO)

Topography:
☐ Hill
☐ Slope
☒ Upland
☐ Valley

17 Water well contractor's certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Layne-Western Co 150
Business name License No.
Address Garden City
Signed [signature] Date 14 May 75
Authorized representative

Forward the white, blue and pink copies to the Kansas State Dept. Of Health.

Form WWC-5

TEST HOLE REPORT

Layne-Western Company, Inc.

WATER SUPPLY SERVICES SINCE 1924

TEST DRILLING • WATER WELLS • PUMPS

P.O. Box 686 - W. Hwy. 50
Garden City, Kansas 67846

Contract Name: Ed Waugh

Job No.: K-491 Date: 3-19-75

City: Weskan State: Kansas

TEST HOLE No. 3-75

Driller: Pargen

Location of Test Hole: 900' North & 760' E of abandoned well or 420' S. & 760' E of NW corner of ¼ SW ¼ Sec. 22 of T 14S, R 42W, Wallace Co., Kansas.

Elevation of Test Hole:

Static Water Level: 145'

Measured: in well Hours After Completion

From	To	Description of Strata	Water Bearing	
0	2	Top soil		
2	60	Tan clay		
60	84	Fine to coarse sand		
84	140	Sandy tan clay		
140	160	Fine to coarse sand medium gravel silty		
160	192	Tan clay		
192	206	Fine to coarse sand medium gravel		
206	260	Tan clay with light sandlenses		
260	360	Fine to coarse sand medium to coarse gravel loose with clay lenses		
360	380	Tan clay with sand streaks		
380	410	Fine to coarse sand medium to coarse gravel loose with clay streaks		
410	420	Black shale		

Remarks: