

USE TYPEWRITER OR BALL POINT PEN. PRESS FIRMLY. PRINT CLEARLY.

WESKAN

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

B3B

Location of well: Wallace
County: Wallace
Fraction: NW 1/4 NW 1/4 NW 1/4
Section number: 23
Township number: T 14 S R 42
Range number: E/W

2. Distance and direction from nearest town or city: 2 1/2 miles south of Weskan, Kansas
Street address of well location in city:
3. Owner of well: Edward Waugh
R.R. or street:
City, state, zip code: Weskan, Kansas

4. Locate with "X" in section below: Sketch map:
N
NW NE
SW SE
S
1 Mile
NW corner of the NW 1/4, Sec. 23, T14S, R42W, Wallace County, Kans.

6. Bore hole dia. 28 in. Completion date
Well depth 385 ft. 2/18/77
7. Cable tool Rotary Driven Dug
Hollow rod Jetted Bored Reverse rotary
8. Use: Domestic Public supply Industry
 Irrigation Air conditioning Stock
Lawn Oil field water Other
9. Casing: Material stl Height: Above or below
Threaded Welded Surface 12 in.
RMP PVC Weight 37 lbs./ft.
Dia 16 in. to 227 ft. depth Wall Thickness: inches or
Dia. in. to ff. depth gage No. 219

5. Type and color of material	From	To
Top soil	0	4
Tan clay, and sand streaks	4	95
Fine to coarse sand	95	107
Tan clay, sand streaks	107	225
Fine to coarse sand, clay streaks	225	246
Very fine sand	246	270
Fine to coarse sand	270	280
Fine to medium sand, clay streaks	280	310
Fine to coarse sand	310	340
Fine sand	340	378
Fine to coarse sand	378	385
Black shale	385	400

10. Screen: Manufacturer's name Cook, Doerr, Foster
Type nw, louver, millslot 16"
Slot/gauze 1/8" Length 160'
Set between 225 ft. and 385 ft.
ft. and ft.
Gravel pack? Size range of material 3.0mm
11. Static water level: mo./day/yr.
150 ft. below land surface Date 12/16/76
12. Pumping level below land surfaces:
212 ft. after 1 hrs. pumping 1991 g.p.m.
ft. after hrs. pumping g.p.m.
Estimated maximum yield 2500 g.p.m.
13. Water sample submitted: mo./day/yr.
Yes No Date
14. Well head completion:
Pitless adapter Inches above grade
15. Well grouted?
With: Neat cement Bentonite Concrete
Depth: From 0 ft. to 10 ft.
16. Nearest source of possible contamination: unk
ft. Direction Type
Well disinfected upon completion? Yes No
17. Pump: Not installed
Manufacturer's name Layne & Bowler
Model number 12 TL HP 200 Volts 460
Length of drop pipe 260 ft. capacity 1500 g.p.m.
Type:
Submersible Turbine
Jet Reciprocating
Centrifugal Other

18. Elevation: 3815 (TOPC)
19. Remarks:
Topography:
Hill
Slope
 Upland
Valley

20. Water well contractor's certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Layne-Western Co., Inc. 102
Business name License No.
Address Garden City, Kansas
Signed: P. J. Vincent Date 22 Feb 77
Authorized representative

14
42
23
Sec
1/4 1/4 1/4