USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY

WESKAN

WATER WELL RECORD
KSA 82a-1201-1215

DBB

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County	Township name	Fraction	Section number	Town number	Range number
	Wallace		NW NW SE	27	14 S	42 W

Distance and direction from nearest town or city: Approx. 4 S 7.5 W. from WesKan

Street address of well location if in city:

3 Owner of well: Robert McKinney

Address: WesKan, Ks

Locate with "X" in section below:

Sketch map:

N, W, E, S, 1 Mile

4 Well depth: 330 ft. Date of completion ____
Well diameter 28 in. 24 May 75

5 ☐ Cable tool ☐ Rotary ☐ Driven ☐ Dug
☐ Hollow rod ☐ Jetted ☐ Bored ☒ Reverse rotary

6 Use: ☐ Domestic ☐ Public supply ☐ Industry
☒ Irrigation ☐ Air conditioning ☐ Commercial
☐ Test well ☐ ____

7 Casing: Material STL Height: above/~~below~~
Threaded ☐ Welded ☒ Surface 12 in.
Diam. Weight 37 lbs./ft.
16 in. to 330 ft. depth Drive shoe? ☐ Yes ☒ No
____ in. to ____ ft. depth

8 Screen:
Manufacturer Dorr T Foster
Type Louver T Mill slot 16"
Slot/gauze 1/8" Length 180'
Set between 150 ft. and 330 ft.
Fittings: 3-10 mm
Gravel pack ☒ Yes ☐ No Size range of material ____

9 Static water level:
136 ft. below land surface Date 3 May 75

10 Pumping level below land surfaces:
153 ft. after 1 hrs. pumping 1683 g.p.m.
159 ft. after 1 hrs. pumping 2318 g.p.m.
Estimated maximum yield 4000 g.p.m.

11 Water sample submitted:
☐ Yes ☒ No Date ____

12 Well head completion:
☐ Pitless adapter ☒ Inches above grade

13 Well grouted? ☒ Yes ☐ No
☐ Neat cement ☒ Bentonite ☐ ____
Depth: From 0 ft. to 10 ft.

14 Nearest source of possible contamination: Unk
ft. ____ Direction ____ Type ____
Well disinfected upon completion? ☒ Yes ☐ No

15 Pump: ☐ Not installed
Manufacturer's name Layne
Model number 12TH HP 150 Volts 480
Length of drop pipe 240 ft. capacity 2100 g.m.p.
Type:
☐ Submersible ☒ Turbine
☐ Jet ☐ Reciprocating
☐ Certrifugal ☐ Other

2 Type and color of material	From	To
Well drilled near TH 4-74 (see		
attached) which is located 600' E		
from the NW cor of the SE ¼,		
Sec 27, 14-42, Wallace Co.		
BROCK 330'		
(use a second sheet if needed)		

16 Remarks: elevation 3806 (TOPO)

Topography:
☐ Hill
☐ Slope
☒ Upland
☐ Valley

17 Water well contractor's certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Business name Layne-Western Co License No. 150
Address Garden City
Signed R L Kimmett Date
Authorized representative 16 Jun 75

Forward the white, blue and pink copies to the Kansas State Dept. Of Health.

Form WWC-5

TEST HOLE REPORT

Layne-Western Company, Inc.

WATER SUPPLY SERVICES SINCE 1924

TEST DRILLING • WATER WELLS • PUMPS

P.O. Box 686 - W. Hwy. 50
Garden City, Kansas 67846

Contract Name: Robert McKinney

Job No.: K-492 Date: 9-25-74

City: Weskan State: Kansas

TEST HOLE No. 4-74

Driller: McIntyre

Location of Test Hole: 600' E of the NW corner of

¼ SE ¼ Sec. 27 of T 14S, R 42W, Wallace Co., Kansas.

Elevation of Test Hole

Static Water Level 136'

Measured in well Hours After Completion

From	To	Description of Strata	Water Bearing	
0	3	Top soil		
3	22	Clay		
22	78	Tan and white clay with sand lenses		
78	104	Fine to coarse sand loose		
104	119	Hard tan clay with sand lenses		
119	225	Fine to coarse sand loose and tight streaks		
225	330	Fine to coarse sand fine to medium gravel tight and loose streaks		
330	350	Black shale		
		Electric log with samples		

Remarks: