

1 LOCATION OF WATER WELL: Fraction	Section Number	Township Number	Range Number
County: Dickinson NW 1/4 NE 1/4 NE 1/4	6	T 14 S	R 5 E/W

Distance and direction from nearest town or city street address of well if located within city?
1 1/2 miles East of Woodbine Ks & 4 miles North & 1 mile East & 3/4 mile North & 1/4 MILE Northwest

2 WATER WELL OWNER: Rod Knopp
 RR#, St. Address, Box #: 1525 Wolf Rd
 City, State, ZIP Code: Woodbine, Kansas 67492
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	ELEVATION:
	6.6 ft.	
	Depth(s) Groundwater Encountered 1 4.0 ft. 2 ft. 3 ft.	
	WELL'S STATIC WATER LEVEL 3.8 ft. below land surface measured on mo/day/yr 1.2 / 1.6 / 0.4	
	Pump test data: Well water was ft. after hours pumping gpm	
	Est. Yield 1.5 gpm: Well water was ft. after hours pumping gpm	
	WELL WATER TO BE USED AS:	
	5 Public water supply 8 Air conditioning 11 Injection well	
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
	2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well	
	Was a chemical/bacteriological sample submitted to Department? Yes No *; If yes, mo/day/yr sample was submitted	
	Water Well Disinfected? Yes * No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued * Clamped
1 Steel 3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC 4 ABS	7 Fiberglass		Threaded
Blank casing diameter 5 in. to 6.6 ft., Dia			
Casing height above land surface 1.5 in., weight	2.0 lbs./ft.	Wall thickness or guage No. 2.5.0	
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	7 PVC	10 Asbestos-Cement
1 Steel 3 Stainless Steel	6 Concrete tile	8 RMP (SR)	11 Other (Specify)
2 Brass 4 Galvanized Steel		9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Guazed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot 3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter 4 Key punched	7 Torch cut	10 Other (specify)	ft.
SCREEN-PERFORATED INTERVALS:	From 3.8 ft. to 6.6 ft.		
GRAVEL PACK INTERVALS:	From 2.2 ft. to 6.6 ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout intervals: From 0 ft. to 2.2 ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well? NONE	DRILLED IN PASTURE			14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				How many feet? NONE WITHIN 1000

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	DARK TOP SOIL			
1	4	BROWN CLAY			
4	17	LIMESTONE			
17	27	LITE COLOR SHALE			
27	30	LITE GRAY SHALE			
30	31	LITE COLOR LIMESTONE			
31	40	LITE COLOR SHALE			
40	52	HARD LIMESTONE			
52	61	HARD GRAY LIMESTONE			
61	65	LITE COLOR LIMESTONE			
65	66	GRAY LIMESTONE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1.2 / 1.6 / 0.4 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 39.7 This Water Well Record was completed on (mo/day/yr) 1.2 / 1.8 / 0.4 under the business name of CENTRAL KANSAS DRILLING by (signature) *David D. Martin*