


1 LOCATION OF WATER WELL: County: RUSSELL	Fraction SE 1/4 SE 1/4 SE 1/4	Section Number 30	Township Number T 15 S	Range Number R 13
---	---	-----------------------------	----------------------------------	-----------------------------

Distance and direction from nearest town or city street address of well if located within city?

6 miles EAST OF MILBERGER, KS**RW-1**

2 WATER WELL OWNER: Carbo, Inc. RR#, St. Address, Box #: 600 North Dairy Ashford City, State, ZIP Code: Houston, Texas 77252	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 29' ft. ELEVATION: Depth(s) Groundwater Encountered: 13.05 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 13.05 ft. below land surface measured on mo/day/yr 2-28-92 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 12 in. to 29 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X
---	--

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter: 5 in. to 10 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface: 12 in., weight lbs./ft. Wall thickness or gauge No. Sch 40 .258 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 9 ft. to 29' ft., From ft. to ft. GRAVEL PACK INTERVALS: From 6.5 ft. to 29' ft., From ft. to ft.
--

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bant pellets Grout Intervals: From 4.5 ft. to 3.5 ft., From 6.5 ft. to 4.5 ft., From 3.5 ft. to 0 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) SELLEN CREEK Direction from well? west How many feet? 250

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Silty Clay			
4	9.5	Sandy Clay w/ Rock Frag.			
9.5	16.5	Silty Clay			
16.5	20	Weathered shale			
20	29	Shale of ls stringers			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-12-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 517 This Water Well Record was completed on (mo/day/yr) 2-2-92 under the business name of Groundwater Technology, Inc. by (signature) Steven R. Mitchell
--