## CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking of incorrect	County: Ruese//
Location listed as:	Location changed to:
Section-Township-Range: 10 - 15 - 14  Fraction (1/4 1/4 1/4): None Given	10-155-14W
Fraction ( 1/4 1/4 1/4): None Given	SE
Other changes: Initial statements:	
Changed to:	
Comments: Site name: Maier	Station.
verification method: Phone call to driller	
	initials: DRL date: 5/18/2004

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

	WATER	WELL RECORD	Form WV	VC-5 KSA	82a-1212 Inv#	1340 MW	# 4	
1 LOCATION OF WATER WELL:	Fraction		Ī	Section Numl	ber Township	Number	Range Number	7
County: Russell	1/4	1/4	1/4	10	<u> </u>	5 S	R 14 E/W	
Distance and direction from nearest town	or city street add	dress of well if locate	ed within c	ty?				
2 WATER WELL OWNER: Kaw Pipeline RR#, St. Address, Box # : 1199 W Wisconsin City, State, ZIP Code : Russell, KS				Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH 4								$\Box$
AN "X" IN SECTION BOX:	epth(s) Groundw /ELL'S STATIC V Pump : st. Yield	ater Encountered NATER LEVEL	1 O ter was ter was 5 Public o 6 Oil field	ft. below landf ff water supply	ft. 2	ft. 3 I on mo/day/yr hours pu hours pu in ning 11	Imping gpr Imping gpr In to f Injection well Other (Specify below)	OFFICE
	•			-				활
		icteriological sample	submitted			-	, mo/day/yr sample was su	
5 TYPE OF BLANK CASING USED:	itted	E Manualta inan	0.00	ncrete tile	Water Well Disinfe		No d Clamped	- ON LY
1 Steel 3 RMP (SR) 2 PVC 4 ABS		<ul><li>5 Wrought iron</li><li>6 Asbestos-Cement</li><li>7 Fiberglass</li></ul>	9 Ot	her (specify b	elow) 	Weld Thre	led	
Blank casing diameter in.								
Casing height above land surface		n., weight						
TYPE OF SCREEN OR PERFORATION N				PVC)		Asbestos-ceme	• • •	
1 Steel 3 Stainless st		5 Fiberglass		RMP (SR)				·   ⊣
2 Brass 4 Galvanized		6 Concrete tile		ABS		None used (or		
SCREEN OR PERFORATION OPENINGS			zed wrappe	d	8 Saw cut		11 None (open hole)	
1 Continuous slo  3 Mill s	slot	6 Wire	wrapped		9 Drilled hole	es		
2 Louvered shutter 4 Key SCREEN-PERFORATED INTERVALS:	punched	7 Torc			10 Other (spe	cify)		$\cdot$
GRAVEL PACK INTERVALS:  6 GROUT MATERIAL: 1 Neat cen	FromFrom	8 ft. to ft. to	25		From	ft. 1	to	t. 30 t.
Grout Intervals: From0ft. What is the nearest source of possible con	entamination:			ft. to8 10 Li	vestock pens	14 A	bandoned water well	t.
1 Septic tank 4 Lateral I		7 Pit privy			uel storage		il well/Gas well	
2 Sewer lines 5 Cess po		8 Sewage lag	goon		ertilizer storage	16 C	Other (specify below)	₹
3 Watertight sewer lines 6 Seepage	e pit	9 Feedyard			secticide storage			·  `
Direction from well? FROM TO	LITUOI OCIC LI	200			many feet?	DI LICCING I	NTEDVALO	4
<u> </u>	LITHOLOGIC LO	JG	FROM	и то		PLUGGING I	INTERVALS	ج SEC.
0 7 Brown Si					<del></del>	,	· · · · · · · · · · · · · · · · · · ·	ن إ—
7 12 Brown Cl. 12 20 Tan/Brow					<del></del>			
					<del> </del>			$\dashv$
20 25 Tan/Grey	_Clay							
								- Z
			_	+				- 5
7 CONTRACTOR'S OR LANDOWNER'S completed on (mo/day/year)	4-00 607	This Water V	Vell Record	and this related and the second and	ecord is true to the	best of my kn	owledge and belief. Kansa	
under the business name of Davis					gnature)	Mau		$\dashv$
INSTRUCTIONS: Use typewriter or ball point pen	PLEASE PRESS FIRE	MLY and PRINT clearly. P	lease fill in bla	nks, underline or o	circle the correct answer	rs. Send top three	copies to Kansas Department	