

WATER WELL RECORD


Form WWC-5

Division of Water Resources App. No.

CORRECTED

1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NW 1/4 1/4 Section Number 19 Township No. T 15 S Range Number R 16 E W
 County: Ellis
 Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here . 8 miles south of Victoria, KS
Global Positioning System (GPS) information:
 Latitude: (in decimal degrees)
 Longitude: (in decimal degrees)
 Elevation:
 Datum: WGS 84, NAD 83, NAD 27
 Collection Method:
 GPS unit (Make/Model:)
 Digital Map/Photo, Topographic Map, Land Survey
 Est. Accuracy: <3 m, 3-5 m, 5-15 m, >15 m

2 WATER WELL OWNER: Westside Managemnet, LLC
 RR#, Street Address, Box #: 562 W. State Rd 4
 City, State, ZIP Code : Olmitz, Ks 67564

3 LOCATE WELL WITH AN "X" IN SECTION BOX:
 N
 W  E
 S
 1 mile

4 DEPTH OF COMPLETED WELL 260 ft.
 Depth(s) Groundwater Encountered (1) 218 ft. (2) ft. (3) ft.
 WELL'S STATIC WATER LEVEL 132 ft. below land surface measured on mo/day/yr. 09/25/12
 Pump test data: Well water was 135 ft. after 10 hours pumping. 15 gpm
 EST. YIELD 15 gpm. Well water was ft. after hours pumping gpm
 Bore Hole Diameter 8 3/4 in. to 260 ft., and in. to ft.
 WELL WATER TO BE USED AS: Public water supply Geothermal Injection well
 Domestic Feedlot Oil field water supply Dewatering Other (Specify below)
 Irrigation Industrial Domestic-lawn & garden Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No
 If yes, mo/day/yr sample was submitted.....
 Water well disinfected? Yes No

5 TYPE OF CASING USED: Steel PVC Other
 CASING JOINTS: Glued Clamped Welded Threaded
 Casing diameter 5 in. to 260 ft., Diameter in. to ft., Diameter in. to ft.
 Casing height above land surface 24 in., Weight 2.91 lbs./ft., Wall thickness or gauge No. 21
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 Steel Stainless Steel PVC Other (Specify)
 Brass Galvanized Steel None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)
 Louvered shutter Key punched Wire wrapped Saw cut Other (specify)
 SCREEN-PERFORATED INTERVALS: From 260 ft. to 230 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 260 ft. to 35 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other
 Grout Intervals: From 30 ft. to 0 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)
 Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well
 Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well
 Direction from well Distance from well

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS
0	3	Top soil			
3	25	Rock & clay			
25	120	Shale			
120	160	Dakota Clay			
160	190	Gray white clay			
190	218	Clay & sand rock layers			
218	253	Sand rock			
253	260	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 09/26/12 and this record is true to the best of my knowledge and belief.
 Kansas Water Well Contractor's License No. 0199 This Water Well Record was completed on (mo/day/year) 10/23/12
 under the business name of Karst Water Well Drilling and Service, I by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. I include fee of \$5.00 for each constructed well. Visit us at <http://www.kdheks.gov/waterwell/index.html>.