			VV/C	TER WELL RECORD	Form \A/I	NC 5 KSA S	220 1212			
1 LOCA	TION OF W	ATER WELL:	Fraction	TEN WELL RECORD	FOITH VV	Section Numb		nip Number	Range Nu	mber
County:			NE	% NE %	SE 1/4	29	1	15 S	R 18	₽ Ø
Distance	and directi	on from nearest t	own or city stre	et address of well if loca	· I				<u> </u>	_ U
		th & W 100' no				•				
				n Commission		-	<u> </u>			
RR# St	Address, B	ox# : 2301 E		ii Commission			Board of /	Varioultura Div	isian of Water D	
	e, ZIP Code		Kansas 6760	1			Application		ision of Water Re	sources
-		LOCATION					• • •			
<u>-7 Wiff)</u>	AN "X" IN S	SECTION BOX:	4 DEPTH OF	COMPLETED WELL	25	ft. EU	EVATION:		1918 . 3	
- -		N		indwater Encountered						
' ≜ [T	WELL'S STATIC WATER LEVEL 10.43 ft. below land surface measured on mo/day/yr 6/10/99							
	NW	NE	Pump test data: Well water was NA ft. after hours pumping gpm							
ı	144.4		Est. Yield NA. gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to ft. and in. to ft							
1 Mile										
		│	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		SE	1 Domest	ic 3 Feedlot 6	Oil field	water supply		•	Other (Specify b	elow)
	SW		2 Irrigatio				_	•		
1			Was a chemical/bacteriological sample submitted to Department: YesNo							pla was
Y L	· · · · · · · · · · · · · · · · · · ·	\	submitted	,			Vater Well Disin		No	
5 TYPE	OF BLANK	CASING USED:	I	5 Wrought iron	8 0	oncrete tile			d Clampe	vd ad
의 ''' 도 1 s		3 RMP (SI		6 Asbestos-Cement		her (specify be			ded Clampe led	
P		4 ABS	7	7 Fiberglass					aded. 🏑	
			:m +a					IIII C		
				12 ft., Dia						
				in., weight						
		OR PERFORATIO				PVC		Asbestos-cem		
1 S		3 Stainless		5 Fiberglass		RMP (SR)	11	Other (specify	·)	:
	rass	4 Galvaniz		6 Concrete tile	9	ABS		None used (or	en hole)	
SCREEN	OR PERFC	RATION OPENIN		5 Gauz	ed wrappe	ed	8 Saw cut		11 None (open	hole)
1 Continuous slot 3 Mill slot 6 Wire wra							9 Drilled hol	es		
2 L	ouvered sh	utter 4 K	ey punched	7 Torch					. 	
SCREEN-	PERFORAT	TED INTERVALS:	From	12 ft. to	22	ft., F	From	ft.	to	ft.
			From	ft. to		ft., F	From	ft.	to	ft.
(GRAVEL PA	ACK INTERVALS:	From	1.02 ft. to		ft, F	From	ft.	to	ft.
			From	ft. to		ft., F	From	ft .	to	ft.
6 GROU	T MATERIA	L: 1 Neat	cement	2 Cement grout	(3) Be	entonite	4 Other			
				ft., From						
		source of possible							bandoned water	
	tic tank	4 Later								weii
	er lines			7 Pit privy					il well/Gas well	,
		5 Cess		8 Sewage lag	oon		rtilizer storage	•	ther (specify bek	
	ertight sew	er lines 6 Seep	age pit	9 Feedyard			ecticide storage	· · · · · · · · · · · · · · · · · · ·	nknown	
FROM	from well?						any feet?			
	10	Tongoil	LITHOLOGIC		FROM	1 10		PLUGGING II	NIERVALS	
0	1	Topsoil,								
1	6	Clay, Brown							·	
6	11	Gravel,								
11	21	Gravel,								
21	23	Gravel,								
23	25	Shale, Dark C	Gray	•						
										:
										·
									····	
										
									······	
							MW1, Aboveg			
							Project Name:	KCC-Ruder Cr	eek	
							GeoCore # 796	, #		

×

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.