


1 LOCATION OF WATER WELL: Fraction SW 1/4 NE 1/4 Section Number 21 Township Number T 15 S Range Number R 18 E/W
 County: Ellis

Distance and direction from nearest town or city street address of well if located within city?
1/2 N of Schoeche on 193 600' West

2 WATER WELL OWNER: Fidelis Eugol
 RR#, St. Address, Box # : 755 2604 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Hayes KS 67601 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 24.5 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 19.8 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 2.0 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 6 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
Bore Hole 9"
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 18.5 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 24 in., weight S.D.R. 21 lbs./ft. Wall thickness or guage No.
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC 10 Asbestos-Cement
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 18.5 ft. to 24.5 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 21 ft. to 24.5 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout Bentonite 4 Other
 Grout Intervals: From 0 ft. to 21 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination: 10 Livestock pens Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? West How many feet? 90'

| FROM | TO | LITHOLOGIC LOG | FROM | TO | PLUGGING INTERVALS |
|------|-----|-------------------------------------|------|-----|------------------------|
| 0 | 8 | Topsoil & Brown Clay | 210 | 247 | Sand with Clay streaks |
| 8 | 20 | Yellow Clay Little Clitche | 247 | | Shale |
| 20 | 22 | Yellow Rock Hard | | | |
| 22 | 27 | White Clay | | | |
| 27 | 60 | Blue Shale | | | |
| 60 | 90 | Blue Shale + Gray Clay Streaks | | | |
| 90 | 125 | Blue Shale + Brown Clay Streaks | | | |
| 125 | 129 | Sand Stone | | | |
| 129 | 135 | Shale Hard | | | |
| 135 | 150 | Shale Soft + Gummy | | | |
| 150 | 165 | Shale with Sand streaks | | | |
| 165 | 195 | Light Gray Clay Little Sand streaks | | | |
| 195 | 200 | Sand Stone | | | |
| 200 | 210 | Light Gray Clay | | | |

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-13-06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 677 This Water Well Record was completed on (mo/day/yr) 6-20-06 under the business name of CLT Inc. by (signature) CT